



## CIR030-22-34P-T12 Information

Heisener.com

**Part Number** CIR030-22-34P-T12 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 5POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CIR030-22-34P-T12 Specifications

Manufacturer Part Number     CIR030-22-34P-T12       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CIR       Connector Type     Receptacle, Male Pins       Number of Positions     5       Shell Size - Insert     22-34       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Solder Cup       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     -       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Gold       Features     -       Voltage - Rated     900VAC, 1250VDC       Current Rating     13A, 23A			
Category Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Onover Alexander  Connectors, Interconnects Circular Connectors MIL-DTL-5015, CIR Receptacle, Male Pins NIL-DTL-5015, CIR Receptacle, Male Pins Passening Septacle, Male Pins  Nell Mounting Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating	Manufacturer Part Number	CIR030-22-34P-T12	
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-34Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A, 23A	Manufacturer	ITT Cannon, LLC	
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-34Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A, 23A	Category	Connectors, Interconnects	
Series MIL-DTL-5015, CIR  Connector Type Receptacle, Male Pins  Number of Positions 5  Shell Size - Insert 22-34  Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection -  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Gold  Features  Voltage - Rated 900VAC, 1250VDC  Current Rating 13A, 23A		Circular Connectors	
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert22-34Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A, 23A	Package	-	
Number of Positions  Shell Size - Insert  22-34  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A, 23A	Series	MIL-DTL-5015, CIR	
Shell Size - Insert 22-34 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Connector Type	Receptacle, Male Pins	
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features - Voltage - Rated 900VAC, 1250VDC  Current Rating 13A, 23A	Number of Positions	5	
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold  Features - Voltage - Rated 900VAC, 1250VDC  Current Rating 13A, 23A	Shell Size - Insert	22-34	
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Shell Size, MIL	-	
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Mounting Type	Panel Mount, Flange	
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Termination	Solder Cup	
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Fastening Type	Bayonet Lock	
Shell Material, Finish  Contact Finish  Gold  Features  Voltage - Rated  Ourrent Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Gold	Orientation	N (Normal)	
Contact Finish Gold Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Ingress Protection	-	
Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated	
Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 23A	Contact Finish	Gold	
Current Rating 13A, 23A	Features	-	
-	Voltage - Rated	900VAC, 1250VDC	
Report errors?	Current Rating	13A, 23A	
			Report errors?

### CIR030-22-34P-T12 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CIR030-22-34P-T12 Payment Methods





















## CIR030-22-34P-T12 Shipping Methods













If you have any question about CIR030-22-34P-T12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com