

Heisener.com

# CIR030-28A-5PF80T108

### CIR030-28A-5PF80T108 Information

Part Number CIR030-28A-5PF80T108

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 5POS PNL MNT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CIR030-28A-5PF80T108 Specifications

Manufacturer Part Number       CIR030-28A-5PF80T108         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CIR         Connector Type       Receptacle, Male Pins         Number of Positions       5         Shell Size - Insert       28-A5         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       -         Shell Material, Finish       Aluminum Alloy, Black Zinc Cobalt Plated         Contact Finish       Silver         Features       -         Voltage - Rated       500VAC, 700VDC         Current Rating       46A		
Category Circular Connectors  Package Package Package MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions Shell Size - Insert Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Voltage - Rated Current Rating 46A	Manufacturer Part Number	CIR030-28A-5PF80T108
Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 28-A5 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert28-A5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert28-A5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert28-A5Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating46A	Package	-
Number of Positions  Shell Size - Insert  28-A5  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Voltage - Rated  500VAC, 700VDC  Current Rating  46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Number of Positions	5
Mounting Type Panel Mount, Flange  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC  Current Rating 46A	Shell Size - Insert	28-A5
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  -  Voltage - Rated  500VAC, 700VDC  Current Rating  46A	Mounting Type	Panel Mount, Flange
Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC  Current Rating 46A	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC  Current Rating 46A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Silver  - 46A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating  Silver  46A	Ingress Protection	-
Features - Voltage - Rated 500VAC, 700VDC Current Rating 46A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC Current Rating 46A	Contact Finish	Silver
Current Rating 46A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	46A
		Report errors?

#### CIR030-28A-5PF80T108 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CIR030-28A-5PF80T108 Payment Methods



















## CIR030-28A-5PF80T108 Shipping Methods













If you have any question about CIR030-28A-5PF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com