



## CIR030-40A-60P Information

Heisener.com

Part Number CIR030-40A-60P Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT MALE 60POS SLVR SLDR

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CIR030-40A-60P Specifications**

Manufacturer Part Number       CIR030-40A-60P         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CIR         Connector Type       Receptacle, Male Pins         Number of Positions       60         Shell Size - Insert       40-A60         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Solder Cup         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       -         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       500VAC, 700VDC         Current Rating       13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer Part Number	CIR030-40A-60P
Package-SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Receptacle, Male Pins Number of Positions 60 Shell Size - Insert 40-A60 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 13A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypeReceptacle, Male PinsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A	Package	-
Number of Positions60Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A	Series	MIL-DTL-5015, CIR
Shell Size - Insert40-A60Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A	Number of Positions	60
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A	Shell Size - Insert	40-A60
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features  - Voltage - Rated 500VAC, 700VDC  Current Rating  13A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  - 13A	Orientation	N (Normal)
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  - Voltage - Rated  500VAC, 700VDC  13A	Ingress Protection	-
Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A	Contact Finish	Silver
Current Rating 13A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A
		Report errors?

#### CIR030-40A-60P Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CIR030-40A-60P Payment Methods**



















## **CIR030-40A-60P Shipping Methods**













If you have any question about CIR030-40A-60P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com