

# **CIR06-22-21SX Information**

Heisener.com

Part Number CIR06-22-21SX Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 3POS STRGHT SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **CIR06-22-21SX Specifications**

Manufacturer Part Number     CIR06-22-21SX       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CIR       Connector Type     Plug, Female Sockets       Number of Positions     3       Shell Size - Insert     22-21       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Bayonet Lock       Orientation     X       Ingress Protection     -       Shell Material, Finish     Aluminum Alloy, Olive Drab Cadmium Plated       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Rating     13A, 150A			
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert22-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationXIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 150A	Manufacturer Part Number	CIR06-22-21SX	
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert22-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationXIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 150A	Manufacturer	ITT Cannon, LLC	
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert22-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationXIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 150A	Category	Connectors, Interconnects	
Series MIL-DTL-5015, CIR  Connector Type Plug, Female Sockets  Number of Positions 3  Shell Size - Insert 22-21  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation X  Ingress Protection -  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 150A		Circular Connectors	
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert22-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationXIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 150A	Package	-	
Number of Positions3Shell Size - Insert22-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationXIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 150A	Series	MIL-DTL-5015, CIR	
Shell Size - Insert22-21Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationXIngress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 150A	Connector Type	Plug, Female Sockets	
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation X Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 150A	Number of Positions	3	
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation X  Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 150A	Shell Size - Insert	22-21	
Termination Solder Cup  Fastening Type Bayonet Lock Orientation X Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 150A	Shell Size, MIL	-	
Fastening Type  Bayonet Lock  Orientation  X  Ingress Protection  - Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  - Voltage - Rated  500VAC, 700VDC  Current Rating  13A, 150A	Mounting Type	Free Hanging (In-Line)	
Orientation X Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 150A	Termination	Solder Cup	
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 150A	Fastening Type	Bayonet Lock	
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver	Orientation	X	
Contact Finish Silver  Features - Voltage - Rated Current Rating 13A, 150A	Ingress Protection	-	
Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 150A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated	
Voltage - Rated 500VAC, 700VDC Current Rating 13A, 150A	Contact Finish	Silver	
Current Rating 13A, 150A	Features	-	
	Voltage - Rated	500VAC, 700VDC	
Report errors?	Current Rating	13A, 150A	
			Report errors?

#### CIR06-22-21SX Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **CIR06-22-21SX Payment Methods**



















# **CIR06-22-21SX Shipping Methods**













If you have any question about CIR06-22-21SX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com