



Heisener.com

#### CIR06-28-11SF80T108 Information

Part Number CIR06-28-11SF80T108
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 22POS STRGHT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CIR06-28-11SF80T108 Specifications

Manufacturer Part NumberCIR06-28-11SF80T108ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating13A, 23A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Manufacturer Part Number	CIR06-28-11SF80T108
Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 22 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features - Voltage - Rated  Convertified  Circular Connectors  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  Alluminum Cloudets  Alluminum Alloy Black Zinc Cobalt Plated  Silver  Features - Voltage - Rated	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 22 Shell Size - Insert 28-11 Shell Size, MIL - Characteria Pree Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - SOOVAC, 700VDC	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions22Shell Size - Insert28-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 22  Shell Size - Insert 28-11  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC	Package	-
Number of Positions  Shell Size - Insert  28-11  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Features  Voltage - Rated  28-11  - Normal  Free Hanging (In-Line)  Free Hanging (In-Line)  Aluminum Crimp  Aluminum Alloy  Sayonet Lock  N (Normal)  - Silver  Features  - SoovAC, 700VDC	Series	MIL-DTL-5015, CIR
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Features  Voltage - Rated  28-11  -  SooVAC, 700VDC	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC	Number of Positions	22
Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated Free Hanging (In-Line)  Auminum Alloy Sayonet Lock N (Normal) - Silver - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Silver - Solver - Solver	Shell Size - Insert	28-11
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  -  Voltage - Rated  SoovAC, 700VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Aluminum Alloy, Black Zinc Cobalt Plated  Silver  -  500VAC, 700VDC	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated 500VAC, 700VDC	Ingress Protection	-
Features - Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
-	Features	-
Current Rating 13A, 23A	Voltage - Rated	500VAC, 700VDC
	Current Rating	13A, 23A
Report errors?		Report errors?

#### CIR06-28-11SF80T108 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CIR06-28-11SF80T108 Payment Methods



















## CIR06-28-11SF80T108 Shipping Methods













If you have any question about CIR06-28-11SF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com