



CIR06AF-24-22P Information

Heisener.com

Part NumberCIR06AF-24-22PManufacturerITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 4POS STRGHT PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR06AF-24-22P Specifications

| Manufacturer Part NumberCIR06AF-24-22PManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating46A | | | |
|---|--------------------------|---|----------------|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDC | Manufacturer Part Number | CIR06AF-24-22P | |
| Package - Series MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Manufacturer | ITT Cannon, LLC | |
| Package - MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Connector Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Category | Connectors, Interconnects | |
| Series MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 24-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | | Circular Connectors | |
| Connector TypePlug, Male PinsNumber of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDC | Package | - | |
| Number of Positions4Shell Size - Insert24-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDC | Series | MIL-DTL-5015, CIR | |
| Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Connector Type | Plug, Male Pins | |
| Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Number of Positions | 4 | |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDC | Shell Size - Insert | 24-22 | |
| Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Shell Size, MIL | - | |
| Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Mounting Type | Free Hanging (In-Line) | |
| Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Termination | Solder Cup | |
| Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Fastening Type | Bayonet Lock | |
| Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Orientation | N (Normal) | |
| Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Ingress Protection | - | |
| Features Cable Clamp Voltage - Rated 900VAC, 1250VDC | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated | |
| Voltage - Rated 900VAC, 1250VDC | Contact Finish | Silver | |
| | Features | Cable Clamp | |
| Current Rating 46A | Voltage - Rated | 900VAC, 1250VDC | |
| | Current Rating | 46A | |
| Report errors? | | | Report errors? |

CIR06AF-24-22P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR06AF-24-22P Payment Methods



















CIR06AF-24-22P Shipping Methods













If you have any question about CIR06AF-24-22P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com