



CIR06CF22-14SF80 Information

Heisener.com

Part Number CIR06CF22-14SF80 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 19POS STRGHT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR06CF22-14SF80 Specifications

Manufacturer Part Number CIR06CF22-14SF80 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer Part Number	CIR06CF22-14SF80
Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated Current Rating 13A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Crimp Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 19 Shell Size - Insert 22-14 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions19Shell Size - Insert22-14Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Package	-
Number of Positions Shell Size - Insert 22-14 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Number of Positions	19
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size - Insert	22-14
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Cable Clamp Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Cable Clamp 13A	Orientation	N (Normal)
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating 13A	Ingress Protection	Environment Proof
Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A	Contact Finish	Silver
Current Rating 13A	Features	Cable Clamp
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A
		Report errors?

CIR06CF22-14SF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR06CF22-14SF80 Payment Methods



















CIR06CF22-14SF80 Shipping Methods













If you have any question about CIR06CF22-14SF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com