

### CIR06F-20-22S Information

Heisener.com

**Part Number** CIR06F-20-22S **Manufacturer** ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 6POS STRGHT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CIR06F-20-22S Specifications**

Manufacturer Part NumberCIR06F-20-22SManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 46AReport errors?	-	
Category Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 20-22 Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated Current Rating 1  Connectors, Interconnects Circular Connectors  - Circular Connectors  AllL-DTL-5015, CIR  - Connectors NIL-DTL-5015, CIR  - Circular Connectors  6  AllL-DTL-5015, CIR  Curent Rating - Consectors  AllL-DTL-5015, CIR  - Connectors  6  AllL-DTL-5015, CIR  Curent Rating - Connectors  6  Curent Rating - Curent Rating	Manufacturer Part Number	CIR06F-20-22S
Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets  Number of Positions 6 Shell Size - Insert 20-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 46A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 46A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR  Connector Type Plug, Female Sockets  Number of Positions 6  Shell Size - Insert 20-22  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 46A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert20-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 46A	Package	-
Number of Positions Shell Size - Insert 20-22 Shell Size, MIL  Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating  13A, 46A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 46A	Number of Positions	6
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 46A	Shell Size - Insert	20-22
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 46A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  500VAC, 700VDC  Current Rating  13A, 46A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 46A	Termination	Solder Cup
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 46A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Cable Clamp Voltage - Rated Current Rating 13A, 46A	Orientation	N (Normal)
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating 13A, 46A	Ingress Protection	Environment Proof
Features Cable Clamp  Voltage - Rated 500VAC, 700VDC  Current Rating 13A, 46A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A, 46A	Contact Finish	Silver
Current Rating 13A, 46A	Features	Cable Clamp
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A, 46A
		Report errors?

#### CIR06F-20-22S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# CIR06F-20-22S Payment Methods



















### **CIR06F-20-22S Shipping Methods**













If you have any question about CIR06F-20-22S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com