

CIR06F-20-29SW Information

Heisener.com

Part Number CIR06F-20-29SW **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 17POS STRGHT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR06F-20-29SW Specifications

Manufacturer Part Number CIR06F-20-29SW Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer Part Number	CIR06F-20-29SW
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Package	-
Number of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Series	MIL-DTL-5015, CIR
Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Number of Positions	17
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A	Shell Size - Insert	20-29
Termination Solder Cup Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Termination	Solder Cup
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Cable Clamp Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Cable Clamp 13A	Orientation	W
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating 13A	Ingress Protection	Environment Proof
Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A	Contact Finish	Silver
Current Rating 13A	Features	Cable Clamp
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A
		Report errors?

CIR06F-20-29SW Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR06F-20-29SW Payment Methods





















CIR06F-20-29SW Shipping Methods













If you have any question about CIR06F-20-29SW, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com