



CIR06F-40-9SW-F80 Information

Heisener.com

Part Number CIR06F-40-9SW-F80 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN PLUG FMALE 47POS SLVR CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR06F-40-9SW-F80 Specifications

Manufacturer Part Number CIR06F-40-9SW-F80 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 47 Shell Size - Insert 40-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions47Shell Size - Insert40-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 23A, 46A	Manufacturer Part Number	CIR06F-40-9SW-F80
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions47Shell Size - Insert40-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 23A, 46A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 47 Shell Size - Insert 40-9 Shell Size, MIL - Crimp Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 11	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions47Shell Size - Insert40-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 23A, 46A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions47Shell Size - Insert40-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationWIngress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated500VAC, 700VDCCurrent Rating13A, 23A, 46A	Package	-
Number of Positions Shell Size - Insert 40-9 Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert 40-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Number of Positions	47
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Shell Size - Insert	40-9
Termination Crimp Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Mounting Type	Free Hanging (In-Line)
Orientation W Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Cable Clamp Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver Cable Clamp 13A, 23A, 46A	Orientation	W
Contact Finish Silver Cable Clamp Voltage - Rated Current Rating 13A, 23A, 46A	Ingress Protection	Environment Proof
Features Cable Clamp Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A, 46A	Contact Finish	Silver
Current Rating 13A, 23A, 46A	Features	Cable Clamp
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A, 23A, 46A
		Report errors?

CIR06F-40-9SW-F80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR06F-40-9SW-F80 Payment Methods



















CIR06F-40-9SW-F80 Shipping Methods













If you have any question about CIR06F-40-9SW-F80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com