

Heisener.com

# CIR06F14S-6SF80T108

### CIR06F14S-6SF80T108 Information

Part Number CIR06F14S-6SF80T108

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 6POS STRGHT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CIR06F14S-6SF80T108 Specifications

Manufacturer Part NumberCIR06F14S-6SF80T108ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zine Cobalt PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated200VAC, 250VDCCurrent Rating13A		
Category Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Cable Clamp Voltage - Rated  Connectors, Interconnects Circular Connectors  HIL  AUIL-DTL-5015, CIR Plug, Female Sockets MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  MIL-DTL-5015, CIR Plug, Female Sockets  Number of Positions  6 Shell Size - Insert  14S-6 Shell	Manufacturer Part Number	CIR06F14S-6SF80T108
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated200VAC, 250VDC	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 200VAC, 250VDC	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 200VAC, 250VDC		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 6  Shell Size - Insert 14S-6  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features Cable Clamp  Voltage - Rated 200VAC, 250VDC	Package	-
Number of Positions Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Voltage - Rated  6 Contact Finish Cable Clamp Voltage - Rated	Series	MIL-DTL-5015, CIR
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Features  Cable Clamp  Voltage - Rated  14S-6  14S-6  14S-6  Aluming (In-Line)  Free Hanging (In-Line)  Free Hanging (In-Line)  Aluminum  Aluminum  Crimp  Free Hanging (In-Line)  Free Hanging (In-Line)  Aluminum  Crimp  Free Hanging (In-Line)  Aluminum  Sayonet Lock  N (Normal)  Environment Proof  Cable Clamp  Voltage - Rated	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features Cable Clamp  Voltage - Rated  200VAC, 250VDC	Number of Positions	6
Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 200VAC, 250VDC	Shell Size - Insert	14S-6
Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver  Features Cable Clamp  Voltage - Rated 200VAC, 250VDC	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  200VAC, 250VDC	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 200VAC, 250VDC	Termination	Crimp
Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  200VAC, 250VDC	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  Aluminum Alloy, Black Zinc Cobalt Plated  Silver  Cable Clamp	Orientation	N (Normal)
Contact Finish Silver Features Cable Clamp Voltage - Rated 200VAC, 250VDC	Ingress Protection	Environment Proof
Features Cable Clamp Voltage - Rated 200VAC, 250VDC	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 200VAC, 250VDC	Contact Finish	Silver
	Features	Cable Clamp
Current Rating 13A	Voltage - Rated	200VAC, 250VDC
	Current Rating	13A
Report errors?		Report errors?

#### CIR06F14S-6SF80T108 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CIR06F14S-6SF80T108 Payment Methods



















## CIR06F14S-6SF80T108 Shipping Methods













If you have any question about CIR06F14S-6SF80T108, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com