

Heisener.com

# CIR06R22-28SF80T104

#### CIR06R22-28SF80T104 Information

Part Number CIR06R22-28SF80T104

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG FMALE 7POS SLVR CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CIR06R22-28SF80T104 Specifications

Manufacturer Part Number     CIR06R22-28SF80T104       Manufacturer     ITT Cannon, LLC       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-5015, CIR       Connector Type     Plug, Female Sockets       Number of Positions     7       Shell Size - Insert     22-28       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Crimp       Fastening Type     Bayonet Lock       Orientation     N (Normal)       Ingress Protection     Environment Proof       Shell Material, Finish     Aluminum Alloy, Black Zinc Cobalt Plated       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Rating     23A		
Category Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 7 Shell Size - Insert 22-28 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Voltage - Rated Current Rating  Circular Connectors  MIL-DTL-5015, CIR Plug, Female Sockets NIL-DTL-5015, CIR Plug, Female Sockets Plug, Female Sockets Plug, Female Sockets Normale Silver Feet Hanging (In-Line) Crimp Fastening Type Bayonet Lock Ni (Normal) Silver Features - Voltage - Rated SooVAC, 700VDC Current Rating	Manufacturer Part Number	CIR06R22-28SF80T104
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions7Shell Size - Insert22-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating23A	Package	-
Number of Positions  Shell Size - Insert  22-28  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Features  Voltage - Rated  500VAC, 700VDC  Current Rating  22-28  Aluminum Alloy, Black Zinc Cobalt Plated  500VAC, 700VDC  Current Rating	Series	MIL-DTL-5015, CIR
Shell Size - Insert 22-28  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Features - Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Number of Positions	7
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 23A	Shell Size - Insert	22-28
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Size, MIL	-
Fastening Type  Bayonet Lock Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Black Zinc Cobalt Plated  Contact Finish  Silver  Features  -  Voltage - Rated  500VAC, 700VDC  Current Rating  23A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Black Zinc Cobalt Plated  Silver  - 200VAC, 700VDC  23A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating  Silver  23A	Ingress Protection	Environment Proof
Features - Voltage - Rated 500VAC, 700VDC Current Rating 23A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 500VAC, 700VDC Current Rating 23A	Contact Finish	Silver
Current Rating 23A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	23A
		Report errors?

#### CIR06R22-28SF80T104 Guarantees



# **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CIR06R22-28SF80T104 Payment Methods





















# CIR06R22-28SF80T104 Shipping Methods













If you have any question about CIR06R22-28SF80T104, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com