



### CIR06R28-22SF80 Information

Heisener.com

Part Number CIR06R28-22SF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 6POS STRGHT SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CIR06R28-22SF80 Specifications

Manufacturer Part Number       CIR06R28-22SF80         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CIR         Connector Type       Plug, Female Sockets         Number of Positions       6         Shell Size - Insert       28-22         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Proof         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       -         Voltage - Rated       900VAC, 1250VDC         Current Rating       13A, 80A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated Current Rating 13A, 80A	Manufacturer Part Number	CIR06R28-22SF80
Circular Connectors  Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Crimp Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CIR  Connector Type Plug, Female Sockets  Number of Positions 6  Shell Size - Insert 28-22  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating 13A, 80A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating13A, 80A	Package	-
Number of Positions  Shell Size - Insert  28-22  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A, 80A	Series	MIL-DTL-5015, CIR
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Crimp  Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A, 80A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver  Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Number of Positions	6
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Bayonet Lock  Orientation N (Normal)  Ingress Protection Environment Proof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating 13A, 80A	Shell Size - Insert	28-22
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  13A, 80A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  -  Voltage - Rated  900VAC, 1250VDC  13A, 80A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Ingress Protection	Environment Proof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 13A, 80A	Contact Finish	Silver
Current Rating 13A, 80A	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	13A, 80A
		Report errors?

## CIR06R28-22SF80 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CIR06R28-22SF80 Payment Methods





















## CIR06R28-22SF80 Shipping Methods













If you have any question about CIR06R28-22SF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com