

CIR08A-36-7P Information

Heisener.com

Part Number CIR08A-36-7P
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN PLUG MALE 47POS SLVR SLDR

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR08A-36-7P Specifications

Manufacturer Part Number CIR08A-36-7P Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 47 Shell Size - Insert 36-7 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 13A, 23A			
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions47Shell Size - Insert36-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Manufacturer Part Number	CIR08A-36-7P	
Package - Series MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 47 Shell Size - Insert 36-7 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Manufacturer	ITT Cannon, LLC	
Package - MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 47 Shell Size - Insert 36-7 Shell Size, MIL - Connector Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - SOOVAC, 700VDC	Category	Connectors, Interconnects	
SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions47Shell Size - Insert36-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC		Circular Connectors	
Connector TypePlug, Male PinsNumber of Positions47Shell Size - Insert36-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Package	-	
Number of Positions Shell Size - Insert 36-7 Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Voltage - Rated 47 36-7 36-7 36-7 36-7 40	Series	MIL-DTL-5015, CIR	
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 36-7 Aluminum Alloy, Right Angle Lock Aluminum Alloy Solder Cup Bayonet Lock N (Normal) Solder Cup Bayonet Lock Solder Cup Bayonet Lock N (Normal) Solder Cup Bayonet Lock Solder Cup Bayonet Lock N (Normal) Solder Cup Bayonet Lock Solder Cup Bayonet Lock N (Normal) Solder Cup Bayonet Lock Solder Cup Bayonet Lock Solder Cup Bayonet Lock Solder Cup Bayonet Lock N (Normal) Solder Cup Bayonet Lock Solder	Connector Type	Plug, Male Pins	
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Solder Cup Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Voltage - Rated 500VAC, 700VDC	Number of Positions	47	
Mounting TypeFree Hanging (In-Line), Right AngleTerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Shell Size - Insert	36-7	
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-	
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Mounting Type	Free Hanging (In-Line), Right Angle	
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup	
Ingress Protection - Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Fastening Type	Bayonet Lock	
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Aluminum Alloy, Olive Drab Cadmium Plated Silver - 500VAC, 700VDC	Orientation	N (Normal)	
Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Ingress Protection	-	
Features - Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated	
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver	
	Features	-	
Current Rating 13A, 23A	Voltage - Rated	500VAC, 700VDC	
2011, 2011	Current Rating	13A, 23A	
Report errors?			Report errors?

CIR08A-36-7P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR08A-36-7P Payment Methods



















CIR08A-36-7P Shipping Methods













If you have any question about CIR08A-36-7P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com