

### CIR08F-22-1P-F80 Information

Heisener.com

**Part Number** CIR08F-22-1P-F80 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Circular Connectors

**Description** CONN PLUG 2POS INLINE PIN RA

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## CIR08F-22-1P-F80 Specifications

Manufacturer Part Number       CIR08F-22-IP-F80         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CIR         Connector Type       Plug, Male Pins         Number of Positions       2         Shell Size - Insert       22-1         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line), Right Angle         Termination       Crimp         Fastening Type       Bayonet Lock         Orientation       N (Normal)         Ingress Protection       Environment Proof         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Cable Clamp         Voltage - Rated       900VAC, 1250VDC         Current Rating       46A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions2Shell Size - Insert22-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating46A	Manufacturer Part Number	CIR08F-22-1P-F80
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions2Shell Size - Insert22-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating46A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 2 Shell Size - Insert 22-1 Shell Size, MIL - Crimp Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 46A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions2Shell Size - Insert22-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating46A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions2Shell Size - Insert22-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating46A	Package	-
Number of Positions2Shell Size - Insert22-1Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 46A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Crimp  Fastening Type Bayonet Lock Orientation N (Normal)  Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Features Cable Clamp  Voltage - Rated 900VAC, 1250VDC  Current Rating 46A	Number of Positions	2
Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesCable ClampVoltage - Rated900VAC, 1250VDCCurrent Rating46A	Shell Size - Insert	22-1
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 46A	Shell Size, MIL	-
Fastening Type  Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Environment Proof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Cable Clamp  Voltage - Rated  900VAC, 1250VDC  Current Rating  46A	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 46A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Cable Clamp Voltage - Rated 900VAC, 1250VDC Current Rating 46A	Fastening Type	Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Cable Clamp  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Cable Clamp  46A	Orientation	N (Normal)
Contact Finish Silver Cable Clamp Voltage - Rated Ourrent Rating  Silver Cable Clamp 46A	Ingress Protection	Environment Proof
Features Cable Clamp  Voltage - Rated 900VAC, 1250VDC  Current Rating 46A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 46A	Contact Finish	Silver
Current Rating 46A	Features	Cable Clamp
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	46A
		Report errors?

#### CIR08F-22-1P-F80 Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## CIR08F-22-1P-F80 Payment Methods


































If you have any question about CIR08F-22-1P-F80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com