



CIR08R24A-28PF80 Information

Heisener.com

Part Number CIR08R24A-28PF80 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 28POS INLINE PIN RA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIR08R24A-28PF80 Specifications

Manufacturer Part Number CIR08R24A-28PF80 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 28 Shell Size - Insert 24-A28 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions28Shell Size - Insert24-A28Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Manufacturer Part Number	CIR08R24A-28PF80
Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 28 Shell Size - Insert 24-A28 Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating Ingress Protection Ingress Protection Silver Fastening Fastening Jah Silver Fastering Jah Silver	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CIR Connector Type Plug, Male Pins Number of Positions 28 Shell Size - Insert 24-A28 Shell Size, MIL - Connector Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 13A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Male PinsNumber of Positions28Shell Size - Insert24-A28Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions28Shell Size - Insert24-A28Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Package	-
Number of Positions28Shell Size - Insert24-A28Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Number of Positions	28
Mounting Type Free Hanging (In-Line), Right Angle Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Shell Size - Insert	24-A28
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Silver - 13A	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - 200VAC, 250VDC 13A	Ingress Protection	Environment Proof
Features - Voltage - Rated 200VAC, 250VDC Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating 13A	Contact Finish	Silver
Current Rating 13A	Features	-
-	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	13A
		Report errors?

CIR08R24A-28PF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIR08R24A-28PF80 Payment Methods



















CIR08R24A-28PF80 Shipping Methods













If you have any question about CIR08R24A-28PF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com