



CIRG06SB22-22ST12 Information

Heisener.com

Part Number CIRG06SB22-22ST12

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects Circular Connectors

Description CONN PLUG 4POS STRGHT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CIRG06SB22-22ST12 Specifications

Manufacturer Part Number Manufacturer CIT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL Mounting Type Free Hanging (In-Line) Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated Current Rating 46A Report errors?		
Category Circular Connectors Package Package Package Plug, Female Sockets Number of Positions Shell Size - Insert Series Aluminum Alloy, Olive Drab Cadmium Plated Contector Type Backage Preatures Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL Fastening Type Free Hanging (In-Line) Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated Voltage - Rated Current Rating 46A	Manufacturer Part Number	CIRG06SB22-22ST12
Circular Connectors Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCoupling Nut, Shielded, Shrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating46A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCoupling Nut, Shielded, Shrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating46A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCoupling Nut, Shielded, Shrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating46A	Package	-
Number of Positions Shell Size - Insert 22-22 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Number of Positions	4
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishGoldFeaturesCoupling Nut, Shielded, Shrink Boot AdapterVoltage - Rated500VAC, 700VDCCurrent Rating46A	Shell Size - Insert	22-22
Termination Solder Cup Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Termination	Solder Cup
Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated Current Rating Aluminum Alloy, Olive Drab Cadmium Plated Gold Coupling Nut, Shielded, Shrink Boot Adapter 500VAC, 700VDC 46A	Orientation	N (Normal)
Contact Finish Gold Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Ingress Protection	Environment Proof
Features Coupling Nut, Shielded, Shrink Boot Adapter Voltage - Rated 500VAC, 700VDC Current Rating 46A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating 46A	Contact Finish	Gold
Current Rating 46A	Features	Coupling Nut, Shielded, Shrink Boot Adapter
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	46A
		Report errors?

CIRG06SB22-22ST12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CIRG06SB22-22ST12 Payment Methods



















CIRG06SB22-22ST12 Shipping Methods













If you have any question about CIRG06SB22-22ST12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com