



CJT1500150RJJ Information

Heisener.com

Part Number CJT1500150RJJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 150 OHM 5% 1500W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CJT1500150RJJ Specifications

Manufacturer Part NumberCJT1500150RJJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRectangular CaseSeriesCJT, CGSResistance150 OhmsTolerance±5%Power (Watts)1500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension19.094" L x 1.969" W (485.00mm x 50.00mm)Height - Seated (Max)4.213" (107.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-Report errors?		
Category Resistors Package Rectangular Case Series CJT, CGS Resistance 150 Ohms Tolerance ±5% Power (Watts) 1500W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer Part Number	CJT1500150RJJ
Package Rectangular Case Series CJT, CGS Resistance 150 Ohms Tolerance ±5% Power (Watts) 1500W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer	TE Connectivity Passive Product
PackageRectangular CaseSeriesCJT, CGSResistance150 OhmsTolerance±5%Power (Watts)1500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension19.094" L x 1.969" W (485.00mm x 50.00mm)Height - Seated (Max)4.213" (107.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Category	Resistors
SeriesCJT, CGSResistance150 OhmsTolerance±5%Power (Watts)1500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension19.094" L x 1.969" W (485.00mm x 50.00mm)Height - Seated (Max)4.213" (107.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-		Chassis Mount Resistors
Resistance150 OhmsTolerance±5%Power (Watts)1500WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension19.094" L x 1.969" W (485.00mm x 50.00mm)Height - Seated (Max)4.213" (107.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Package	Rectangular Case
Tolerance ±5% Power (Watts) 1500W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Series	CJT, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Resistance	150 Ohms
Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Power (Watts)	1500W
Operating Temperature Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Vire Leads Package / Case Rectangular Case Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) Lead Style Package / Case Rectangular Case Failure Rate Flanges Flanges Uther March 19.094" L x 1.969" W (485.00mm x 50.00mm) 4.213" (107.00mm) Wire Leads Rectangular Case -	Features	-
Size / Dimension 19.094" L x 1.969" W (485.00mm x 50.00mm) Height - Seated (Max) 4.213" (107.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 4.213" (107.00mm) Wire Leads Rectangular Case -	Mounting Feature	Flanges
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	19.094" L x 1.969" W (485.00mm x 50.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	4.213" (107.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

CJT1500150RJJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CJT1500150RJJ Payment Methods





















CJT1500150RJJ Shipping Methods













If you have any question about CJT1500150RJJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com