



CJT30039RJJ Information

Heisener.com

Part Number CJT30039RJJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 39 OHM 5% 300W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CJT30039RJJ Specifications

Manufacturer Part Number CJT30039RJJ Manufacturer TE Connectivity Passive Product Category Resistors Package Rectangular Case Series CJT, CGS Resistance 39 Ohms Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -		
Category Resistors Package Rectangular Case Series CJT, CGS Resistance 39 Ohms Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer Part Number	CJT30039RJJ
Chassis Mount Resistors Package Rectangular Case CJT, CGS Resistance 39 Ohms Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate CJT, CGS Rectangular Case Aluminum Aluminum Aluminum Aluminum Bounting Feature Flanges Size / Dimension Rectangular Case Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRectangular CaseSeriesCJT, CGSResistance39 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension8.465" L x 2.362" W (215.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Category	Resistors
SeriesCJT, CGSResistance39 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension8.465" L x 2.362" W (215.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-		Chassis Mount Resistors
Resistance39 OhmsTolerance±5%Power (Watts)300WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension8.465" L x 2.362" W (215.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Package	Rectangular Case
Tolerance ±5% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Series	CJT, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Failure Rate -	Resistance	39 Ohms
Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Power (Watts)	300W
Operating Temperature Features Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Package / Case Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Package / Case Rectangular Case Failure Rate -	Features	-
Size / Dimension 8.465" L x 2.362" W (215.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 1.181" (30.00mm) Wire Leads Rectangular Case -	Mounting Feature	Flanges
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	8.465" L x 2.362" W (215.00mm x 60.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	1.181" (30.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

CJT30039RJJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CJT30039RJJ Payment Methods



















CJT30039RJJ Shipping Methods













If you have any question about CJT30039RJJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com