



CJT40039RJJ Information

Heisener.com

Part Number CJT40039RJJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 39 OHM 5% 400W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CJT40039RJJ Specifications

Manufacturer Part NumberCJT40039RJJManufacturerTE Connectivity Passive ProductCategoryResistorsChassis Mount ResistorsPackageRectangular CaseSeriesCJT, CGSResistance39 OhmsTolerance±5%Power (Watts)400WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension10.433" L x 2.362" W (265.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-Report errors?		
CategoryResistorsPackageRectangular CaseSeriesCJT, CGSResistance39 OhmsTolerance±5%Power (Watts)400WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension10.433" L x 2.362" W (265.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Manufacturer Part Number	CJT40039RJJ
Chassis Mount Resistors Package Rectangular Case Series CJT, CGS Resistance 39 Ohms Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate	Manufacturer	TE Connectivity Passive Product
PackageRectangular CaseSeriesCJT, CGSResistance39 OhmsTolerance±5%Power (Watts)400WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension10.433" L x 2.362" W (265.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Category	Resistors
Series CJT, CGS Resistance 39 Ohms Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -		Chassis Mount Resistors
Resistance 39 Ohms Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Package	Rectangular Case
Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Series	CJT, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Resistance	39 Ohms
Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Power (Watts)	400W
Operating Temperature Features Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Package / Case Rectangular Case Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Package / Case Rectangular Case Failure Rate Failure Rate	Features	-
Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 1.181" (30.00mm) Wire Leads Rectangular Case -	Mounting Feature	Flanges
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	10.433" L x 2.362" W (265.00mm x 60.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	1.181" (30.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

CJT40039RJJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CJT40039RJJ Payment Methods



















CJT40039RJJ Shipping Methods













If you have any question about CJT40039RJJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com