



CJT4003R3JJ Information

Heisener.com

Part Number CJT4003R3JJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 3.3 OHM 5% 400W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CJT4003R3JJ Specifications

Manufacturer Part Number CJT4003R3JJ Manufacturer TE Connectivity Passive Product Category Resistors Chassis Mount Resistors Package Rectangular Case Series CJT, CGS Resistance 3.3 Ohms Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -		
Category Resistors Package Rectangular Case Series CJT, CGS Resistance 3.3 Ohms Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer Part Number	CJT4003R3JJ
Chassis Mount Resistors Package Rectangular Case Series CJT, CGS Resistance 3.3 Ohms Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer	TE Connectivity Passive Product
Package Rectangular Case Series CJT, CGS Resistance 3.3 Ohms Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Category	Resistors
SeriesCJT, CGSResistance3.3 OhmsTolerance±5%Power (Watts)400WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension10.433" L x 2.362" W (265.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-		Chassis Mount Resistors
Resistance3.3 OhmsTolerance±5%Power (Watts)400WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension10.433" L x 2.362" W (265.00mm x 60.00mm)Height - Seated (Max)1.181" (30.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Package	Rectangular Case
Tolerance ±5% Power (Watts) 400W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Series	CJT, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Package / Case Rectangular Case Failure Rate -	Resistance	3.3 Ohms
Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Power (Watts)	400W
Operating Temperature Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Package / Case Rectangular Case Failure Rate	Features	-
Size / Dimension 10.433" L x 2.362" W (265.00mm x 60.00mm) Height - Seated (Max) 1.181" (30.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 1.181" (30.00mm) Wire Leads Rectangular Case -	Mounting Feature	Flanges
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	10.433" L x 2.362" W (265.00mm x 60.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	1.181" (30.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

CJT4003R3JJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CJT4003R3JJ Payment Methods

































If you have any question about CJT4003R3JJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com