

CJT60330RJJ

uest a Quote

CJT60330RJJ Information

Heisener.com	Part Number	CJT60330RJJ	
	Manufacturer	TE Connectivity Passive Product	
	Category	Resistors Chassis Mount Resistors	3
	Description	RES CHAS MNT 330 OHM 5% 60W	
	Package	Rectangular Case	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CJT60330RJJ Specifications

ManufacturerTE Connectivity Passive ProductCategoryResistorsChassis Mount ResistorsPackageRectangular CaseSeriesCJT, CGSResistance330 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular Case			
CategoryResistorsPackageRectangular CasePackageCJT, CGSResistance330 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTomperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)O,787" (20.00mm)Lead StyleRectangular CaseFailure RateIFailure RateI </td <td>Manufacturer Part Number</td> <td>CJT60330RJJ</td>	Manufacturer Part Number	CJT60330RJJ	
Chassis Mount ResistorsPackageRectangular CaseSeriesCJT, CGSResistance330 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.787" (20.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleRectangular CaseFailure Rate-	Manufacturer	TE Connectivity Passive Product	
PackageRectangular CaseSeriesCJT, CGSResistance330 OhmsTolerance5%Power (Wats)60WCompositionWirewoundComposition440ppm/°COperating Temperature-Potance-Features-Cotating, Housing TypeAluminumMounting Feature1528" L x 1.575" W (115.00mm x 40.00mm)Size / Dimension0.787" (20.00mm)Height - Seated (Max)Wire LeadsPackage / CaseRectangular CaseFalure Rate-	Category	Resistors	
SeriesCJT, CGSResistance330 OhmsTolerance±5%Power (Wats)60WCompositionWirewoundTemperature Coefficient±440pm/°COperating Temperature-Cotaing, Housing TypeAluminumNounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)Or87" (20.00mm)Lead StyleWire LeadsPakage / CaseActing L CaseFailure RateOrage / CaseFailure Rate-Failure Rate- <td></td> <td>Chassis Mount Resistors</td>		Chassis Mount Resistors	
Resistance330 OhmsTolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleRectangular CasePackage / Case-Failure Rate-	Package	Rectangular Case	
Tolerance±5%Power (Watts)60WCompositionWirewoundTemperature Coefficient±440pm/°COperating Temperature-Features-Coating, Housing TypeAluninumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)Ors7" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Series	CJT, CGS	
Power (Watts)60WPower (Watts)60WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Resistance	330 Ohms	
CompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFainer Rate-	Tolerance	$\pm 5\%$	
Temperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Power (Watts)	60W	
Operating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Composition	Wirewound	
Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Temperature Coefficient	±440ppm/°C	
Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Operating Temperature	-	
Mounting FeatureFlangesSize / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Features	-	
Size / Dimension4.528" L x 1.575" W (115.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Coating, Housing Type	Aluminum	
Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Mounting Feature	Flanges	
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	4.528" L x 1.575" W (115.00mm x 40.00mm)	
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	0.787" (20.00mm)	
Failure Rate -	Lead Style	Wire Leads	
	Package / Case	Rectangular Case	
Report errors?	Failure Rate	-	
		Report errors?	

CJT60330RJJ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CJT60330RJJ Payment Methods



CJT60330RJJ Shipping Methods



If you have any question about CJT60330RJJ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com