



### **CJT8002R7JJ Information**

Heisener.com

Part Number CJT8002R7JJ

Manufacturer TE Connectivity Passive Product

Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 2.7 OHM 5% 800W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CJT8002R7JJ Specifications**

Manufacturer Part NumberCJT8002R7JJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRectangular CaseSeriesCJT, CGSResistance2.7 OhmsTolerance±5%Power (Watts)800WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension15.748" L x 2.402" W (400.00mm x 61.00mm)Height - Seated (Max)2.323" (59.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-		
CategoryResistorsPackageRectangular CaseSeriesCJT, CGSResistance2.7 OhmsTolerance±5%Power (Watts)800WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension15.748" L x 2.402" W (400.00mm x 61.00mm)Height - Seated (Max)2.323" (59.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Manufacturer Part Number	CJT8002R7JJ
Chassis Mount Resistors  Package Rectangular Case  CJT, CGS  Resistance 2.7 Ohms  Tolerance ±5% Power (Watts) 800W  Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer	TE Connectivity Passive Product
PackageRectangular CaseSeriesCJT, CGSResistance2.7 OhmsTolerance±5%Power (Watts)800WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension15.748" L x 2.402" W (400.00mm x 61.00mm)Height - Seated (Max)2.323" (59.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Category	Resistors
Series         CJT, CGS           Resistance         2.7 Ohms           Tolerance         ±5%           Power (Watts)         800W           Composition         Wirewound           Temperature Coefficient         ±440ppm/°C           Operating Temperature         -           Features         -           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         15.748" L x 2.402" W (400.00mm x 61.00mm)           Height - Seated (Max)         2.323" (59.00mm)           Lead Style         Wire Leads           Package / Case         Rectangular Case           Failure Rate         -		Chassis Mount Resistors
Resistance 2.7 Ohms Tolerance ±5% Power (Watts) 800W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Package	Rectangular Case
Tolerance ±5%  Power (Watts) 800W  Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max) 2.323" (59.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Series	CJT, CGS
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±440ppm/°C  Operating Temperature  -  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max)  Lead Style  Wire Leads  Package / Case  Rectangular Case  Failure Rate  -	Resistance	2.7 Ohms
Composition Wirewound  Temperature Coefficient ±440ppm/°C  Operating Temperature - Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max) 2.323" (59.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C  Operating Temperature -  Features -  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max) 2.323" (59.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Power (Watts)	800W
Operating Temperature  Features  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max)  2.323" (59.00mm)  Lead Style  Wire Leads  Package / Case  Rectangular Case  Failure Rate  -	Composition	Wirewound
Features - Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max) 2.323" (59.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type  Mounting Feature  Flanges  Size / Dimension  15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max)  2.323" (59.00mm)  Lead Style  Wire Leads  Package / Case  Rectangular Case  Failure Rate  -	Operating Temperature	-
Mounting Feature  Size / Dimension  15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max)  Lead Style  Package / Case  Failure Rate  Flanges  Via 400.00mm x 61.00mm)  Lead Style  Wire Leads  Rectangular Case  -	Features	-
Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm)  Height - Seated (Max) 2.323" (59.00mm)  Lead Style Wire Leads  Package / Case Rectangular Case  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Failure Rate  2.323" (59.00mm)  Wire Leads  Rectangular Case  -	Mounting Feature	Flanges
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	15.748" L x 2.402" W (400.00mm x 61.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	2.323" (59.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

#### **CJT8002R7JJ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CJT8002R7JJ Payment Methods**



















# **CJT8002R7JJ Shipping Methods**













If you have any question about CJT8002R7JJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com