



CJT8008R2JJ Information

Heisener.com

Part Number CJT8008R2JJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 8.2 OHM 5% 800W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CJT8008R2JJ Specifications

Manufacturer Part NumberCJT8008R2JJManufacturerTE Connectivity Passive ProductCategoryResistorsPackageRectangular CaseSeriesCJT, CGSResistance8.2 OhmsTolerance±5%Power (Watts)800WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension15.748" L x 2.402" W (400.00mm x 61.00mm)Height - Seated (Max)2.323" (59.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-		
CategoryResistorsPackageRectangular CaseSeriesCJT, CGSResistance8.2 OhmsTolerance±5%Power (Watts)800WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension15.748" L x 2.402" W (400.00mm x 61.00mm)Height - Seated (Max)2.323" (59.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Manufacturer Part Number	CJT8008R2JJ
Chassis Mount Resistors Package Rectangular Case CJT, CGS Resistance Resistance 8.2 Ohms Tolerance ±5% Power (Watts) Remover (Watts) Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer	TE Connectivity Passive Product
PackageRectangular CaseSeriesCJT, CGSResistance8.2 OhmsTolerance±5%Power (Watts)800WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension15.748" L x 2.402" W (400.00mm x 61.00mm)Height - Seated (Max)2.323" (59.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Category	Resistors
Series CJT, CGS Resistance 8.2 Ohms Tolerance ±5% Power (Watts) 800W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -		Chassis Mount Resistors
Resistance 8.2 Ohms Tolerance ±5% Power (Watts) 800W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Package	Rectangular Case
Tolerance ±5% Power (Watts) 800W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Series	CJT, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Resistance	8.2 Ohms
Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Power (Watts)	800W
Operating Temperature Features Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Operating Temperature	-
Mounting Feature Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) Lead Style Package / Case Failure Rate Flanges Flanges University 15.748" L x 2.402" W (400.00mm x 61.00mm) Wire Leads Rectangular Case -	Features	-
Size / Dimension 15.748" L x 2.402" W (400.00mm x 61.00mm) Height - Seated (Max) 2.323" (59.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Failure Rate 2.323" (59.00mm) Wire Leads Rectangular Case -	Mounting Feature	Flanges
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	15.748" L x 2.402" W (400.00mm x 61.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	2.323" (59.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

CJT8008R2JJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CJT8008R2JJ Payment Methods


































If you have any question about CJT8008R2JJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com