



## **CKB.M16.NYMN Information**

Heisener.com

Part Number CKB.M16.NYMN

Manufacturer LEMO

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** RCPT PNL MNT 16SKT CRIMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **CKB.M16.NYMN Specifications**

| Manufacturer Part Number       CKB.M16.NYMN         Manufacturer       LEMO         Category       Connectors, Interconnects         Package       -         Series       2P         Connector Type       Receptacle, Female Sockets         Number of Positions       16         Shell Size - Insert       M16         Shell Size, MIL       -         Mounting Type       Panel Mount - Front and Rear Side Nut         Termination       Crimp         Fastening Type       Push-Pull, Detent Lock         Orientation       B         Ingress Protection       IP50 - Dust Protected         Shell Material, Finish       Polysulfone (PSU)         Contact Finish       Gold         Features       -         Voltage - Rated       -         Current Rating       6A |                          |                                       |
|--|--------------------------|---------------------------------------|
| CategoryConnectors, InterconnectsPackage-Series2PConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - InsertM16Shell Size, MIL-Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A  | Manufacturer Part Number | CKB.M16.NYMN                          |
| Package-Series2PConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - InsertM16Shell Size, MIL-Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A   | Manufacturer             | LEMO                                  |
| Package-Series2PConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - InsertM16Shell Size, MIL-Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A   | Category                 | Connectors, Interconnects             |
| Series2PConnector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - InsertM16Shell Size, MIL-Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A   |                          | Circular Connectors                   |
| Connector TypeReceptacle, Female SocketsNumber of Positions16Shell Size - InsertM16Shell Size, MIL-Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A   | Package                  | -                                     |
| Number of Positions16Shell Size - InsertM16Shell Size, MIL-Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A   | Series                   | 2P                                    |
| Shell Size - InsertM16Shell Size, MIL-Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A  | Connector Type           | Receptacle, Female Sockets            |
| Shell Size, MIL  Mounting Type Panel Mount - Front and Rear Side Nut  Crimp Fastening Type Push-Pull, Detent Lock Orientation B Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU)  Contact Finish Gold Features Voltage - Rated Current Rating 6A  | Number of Positions      | 16                                    |
| Mounting TypePanel Mount - Front and Rear Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationBIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolysulfone (PSU)Contact FinishGoldFeatures-Voltage - Rated-Current Rating6A  | Shell Size - Insert      | M16                                   |
| Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation B Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 6A   | Shell Size, MIL          | -                                     |
| Fastening Type  Orientation  B  Ingress Protection  IP50 - Dust Protected  Shell Material, Finish  Polysulfone (PSU)  Contact Finish  Gold  Features  -  Voltage - Rated  Current Rating  Push-Pull, Detent Lock  B  Current Lock  Push-Pull, Detent Lock  B  Cursent Lock  Polysulfone  (PSU)  Gold  -  Cold  Gold  Gold  Gold  Gold  Gold  Gold  Current Rating  | Mounting Type            | Panel Mount - Front and Rear Side Nut |
| Orientation B Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU) Contact Finish Gold Features - Voltage - Rated - Current Rating 6A   | Termination              | Crimp                                 |
| Ingress Protection IP50 - Dust Protected Shell Material, Finish Polysulfone (PSU)  Contact Finish Gold  Features -  Voltage - Rated -  Current Rating 6A   | Fastening Type           | Push-Pull, Detent Lock                |
| Shell Material, Finish Polysulfone (PSU)  Contact Finish Gold  Features -  Voltage - Rated -  Current Rating 6A  | Orientation              | В                                     |
| Contact Finish Gold Features - Voltage - Rated - Current Rating 6A   | Ingress Protection       | IP50 - Dust Protected                 |
| Features - Voltage - Rated - Current Rating 6A   | Shell Material, Finish   | Polysulfone (PSU)                     |
| Voltage - Rated - Current Rating 6A  | Contact Finish           | Gold                                  |
| Current Rating 6A  | Features                 | -                                     |
|  | Voltage - Rated          | -                                     |
| Report errors?   | Current Rating           | 6A                                    |
|  |                          | Report errors?                        |

#### **CKB.M16.NYMN Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **CKB.M16.NYMN Payment Methods**



















## **CKB.M16.NYMN Shipping Methods**













If you have any question about CKB.M16.NYMN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com