



CKL12BTW01-031 Information



For Reference Only

Part Number CKL12BTW01-031
Manufacturer NKK Switches
Category Switches

Keylock Switches

Description SWITCH KEYLOCK 2POS SPDT 3A 250V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CKL12BTW01-031 Specifications

Manufacturer Part Number CKL12BTW01-031 Manufacturer NKK Switches Category Switches Package - Series CK Circuit SPDT Number of Positions 2 Switch Function On-On Contact Timing Non-Shorting (BBM) Current Rating 3A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Actuator Type Tubular Key Key Removable Positions 1 only Angle of Throw 90° Contact Material Silver (Ag) Contact Finish Silver Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.00mm Dia Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesCKCircuitSPDTNumber of Positions2Switch FunctionOn-OnContact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsEpoxy Sealed Terminals	Manufacturer Part Number	CKL12BTW01-031
Rackage-SeriesCKCircuitSPDTNumber of Positions2Switch FunctionOn-OnContact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Manufacturer	NKK Switches
Package-SeriesCKCircuitSPDTNumber of Positions2Switch FunctionOn-OnContact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Category	Switches
SeriesCKCircuitSPDTNumber of Positions2Switch FunctionOn-OnContact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals		Keylock Switches
CircuitSPDTNumber of Positions2Switch FunctionOn-OnContact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Package	-
Number of Positions2Switch FunctionOn-OnContact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Series	CK
Switch FunctionOn-OnContact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Circuit	SPDT
Contact TimingNon-Shorting (BBM)Current Rating3A (AC)Voltage Rating - AC250VVoltage Rating - DC-Actuator TypeTubular KeyKey Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Number of Positions	2
Current Rating 3A (AC) Voltage Rating - AC 250V Voltage Rating - DC - Actuator Type Tubular Key Key Removable Positions 1 only Angle of Throw 90° Contact Material Silver (Ag) Contact Finish Silver Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.00mm Dia Features Epoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - AC Voltage Rating - DC - Actuator Type Tubular Key Key Removable Positions 1 only Angle of Throw 90° Contact Material Silver (Ag) Contact Finish Silver Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Features 250V 250V Subver Fubular Key Suburates 1 only 90° Silver (Ag) Silver Solder Lug Circular - 19.00mm Dia Epoxy Sealed Terminals	Contact Timing	Non-Shorting (BBM)
Voltage Rating - DC Actuator Type Tubular Key Key Removable Positions 1 only Angle of Throw 90° Contact Material Silver (Ag) Contact Finish Silver Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 19.00mm Dia Epoxy Sealed Terminals	Current Rating	3A (AC)
Actuator Type Key Removable Positions 1 only Angle of Throw 90° Contact Material Silver (Ag) Contact Finish Silver Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 19.00mm Dia Features Tubular Key Tubular Key Tubular Key Tubular Key Tonly Solver 90° Silver (Ag) Silver Solder Lug Panel Mount Epoxy Sealed Terminals	Voltage Rating - AC	250V
Key Removable Positions1 onlyAngle of Throw90°Contact MaterialSilver (Ag)Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Voltage Rating - DC	-
Angle of Throw 90° Contact Material Silver (Ag) Contact Finish Silver Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.00mm Dia Features Epoxy Sealed Terminals	Actuator Type	Tubular Key
Contact Material Contact Finish Silver Silver Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.00mm Dia Features Epoxy Sealed Terminals	Key Removable Positions	1 only
Contact Finish Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.00mm Dia Features Epoxy Sealed Terminals	Angle of Throw	90°
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeaturesEpoxy Sealed Terminals	Contact Material	Silver (Ag)
Termination Style Solder Lug Panel Cutout Dimensions Circular - 19.00mm Dia Features Epoxy Sealed Terminals	Contact Finish	Silver
Panel Cutout Dimensions Circular - 19.00mm Dia Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Features Epoxy Sealed Terminals	Termination Style	Solder Lug
	Panel Cutout Dimensions	Circular - 19.00mm Dia
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

CKL12BTW01-031 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CKL12BTW01-031 Payment Methods



















CKL12BTW01-031 Shipping Methods













If you have any question about CKL12BTW01-031, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com