

# CKR11BX101KP

### **CKR11BX101KP Information**

Heisener.com

Part Number CKR11BX101KP

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

**Description** CAP CER 100PF 100V 10% AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CKR11BX101KP Specifications**

Manufacturer         CKR11BX101KP           Manufacturer         KEMET           Category         Capacitors           Package         Axial, Can           Series         Military, MIL-PRF-39014, CKR11           Capacitance         100pF           Tolerance         ±10%           Voltage - Rated         100V           Temperature Coefficient         BX           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         P (0.1%)           Mounting Type         Through Hole           Package / Case         Axial, Can           Size / Dimension         0.090" Dia x 0.160" L (2.29mm x 4.06mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         Axial, Can           Series         Military, MIL-PRF-39014, CKR11           Capacitance         100pF           Tolerance         ±10%           Voltage - Rated         100V           Temperature Coefficient         BX           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         P (0.1%)           Mounting Type         Through Hole           Package / Case         Axial, Can           Size / Dimension         0.090" Dia x 0.160" L (2.29mm x 4.06mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	CKR11BX101KP
Package         Axial, Can           Series         Military, MIL-PRF-39014, CKR11           Capacitance         100pF           Tolerance         ±10%           Voltage - Rated         100V           Temperature Coefficient         BX           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         P (0.1%)           Mounting Type         Through Hole           Package / Case         Axial, Can           Size / Dimension         0.090" Dia x 0.160" L (2.29mm x 4.06mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer	KEMET
Package         Axial, Can           Series         Military, MIL-PRF-39014, CKR11           Capacitance         100pF           Tolerance         ±10%           Voltage - Rated         100V           Temperature Coefficient         BX           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         P (0.1%)           Mounting Type         Through Hole           Package / Case         Axial, Can           Size / Dimension         0.090" Dia x 0.160" L (2.29mm x 4.06mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         Military, MIL-PRF-39014, CKR11           Capacitance         100pF           Tolerance         ±10%           Voltage - Rated         100V           Temperature Coefficient         BX           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         P (0.1%)           Mounting Type         Through Hole           Package / Case         Axial, Can           Size / Dimension         0.090" Dia x 0.160" L (2.29mm x 4.06mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         100pF           Tolerance         ±10%           Voltage - Rated         100V           Temperature Coefficient         BX           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         P (0.1%)           Mounting Type         Through Hole           Package / Case         Axial, Can           Size / Dimension         0.090" Dia x 0.160" L (2.29mm x 4.06mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Package	Axial, Can
Tolerance ±10%  Voltage - Rated 100V  Temperature Coefficient BX  Operating Temperature -55°C ~ 125°C  Features Military  Ratings -  Applications General Purpose  Failure Rate P (0.1%)  Mounting Type Through Hole  Package / Case Axial, Can  Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Series	Military, MIL-PRF-39014, CKR11
Voltage - Rated100 VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateP (0.1%)Mounting TypeThrough HolePackage / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	100pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate P (0.1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension O.090" Dia x 0.160" L (2.29mm x 4.06mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style  BX  Military  General Purpose Ceneral Purpose  Failure Rate P (0.1%)  General Purpose P (0.1%)  General Purpose  Failure Rate P (0.1%)	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateP (0.1%)Mounting TypeThrough HolePackage / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	100V
Features Military  Ratings - Applications General Purpose Failure Rate P (0.1%)  Mounting Type Through Hole  Package / Case Axial, Can  Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -  Military  General Purpose  Avial, Can  1	Temperature Coefficient	BX
Ratings - General Purpose Failure Rate P (0.1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm) Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate P (0.1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	Military
Failure Rate P (0.1%)  Mounting Type Through Hole  Package / Case Axial, Can  Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Ratings	-
Mounting Type Through Hole  Package / Case Axial, Can  Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)  Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Applications	General Purpose
Package / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Failure Rate	P (0.1%)
Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package / Case	Axial, Can
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.090" Dia x 0.160" L (2.29mm x 4.06mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### **CKR11BX101KP Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CKR11BX101KP Payment Methods**



















### **CKR11BX101KP Shipping Methods**













If you have any question about CKR11BX101KP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com