



CKR11BX472KM Information

Heisener.com

Part Number CKR11BX472KM

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 4700PF 100V 10% AXIAL

Package Axial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CKR11BX472KM Specifications

Manufacturer Part NumberCKR11BX472KMManufacturerKEMETCategoryCapacitorsPackageAxial, CanSeriesMilitary, MIL-PRF-39014, CKR11Capacitance4700pFTolerance±10%Voltage - Rated100VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)		
Category Capacitors Package Axial, Can Series Military, MIL-PRF-39014, CKR11 Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Manufacturer Part Number	CKR11BX472KM
PackageAxial, CanSeriesMilitary, MIL-PRF-39014, CKR11Capacitance4700pFTolerance±10%Voltage - Rated100VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Manufacturer	KEMET
PackageAxial, CanSeriesMilitary, MIL-PRF-39014, CKR11Capacitance4700pFTolerance±10%Voltage - Rated100VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Category	Capacitors
SeriesMilitary, MIL-PRF-39014, CKR11Capacitance4700pFTolerance±10%Voltage - Rated100VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)		Ceramic Capacitors
Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Package	Axial, Can
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Series	Military, MIL-PRF-39014, CKR11
Voltage - Rated100VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / CaseAxial, CanSize / Dimension0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Capacitance	4700pF
Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension BX Operating Temperature -55°C ~ 125°C Military General Purpose Through Hole Ackage / Case Axial, Can 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Tolerance	$\pm 10\%$
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension -55°C ~ 125°C Military Military Through Hole -25°C ~ 125°C Military Through Hole -260°C ~ 125°C Military Through Hole -270°C ~ 125°C Throu	Voltage - Rated	100V
Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Temperature Coefficient	BX
Ratings - General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension O.090" Dia x 0.160" L (2.29mm x 4.06mm)	Features	Military
Failure Rate M (1%) Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Ratings	-
Mounting Type Through Hole Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Applications	General Purpose
Package / Case Axial, Can Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Failure Rate	M (1%)
Size / Dimension 0.090" Dia x 0.160" L (2.29mm x 4.06mm)	Mounting Type	Through Hole
	Package / Case	Axial, Can
Height Control (Mary)	Size / Dimension	0.090" Dia x 0.160" L (2.29mm x 4.06mm)
rieigiii - Seated (Max)	Height - Seated (Max)	-
Thickness (Max) -	Thickness (Max)	-
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

CKR11BX472KM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CKR11BX472KM Payment Methods



















CKR11BX472KM Shipping Methods













If you have any question about CKR11BX472KM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com