



CKR22BX472KM Information



For Reference Only

Part Number CKR22BX472KM
Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 4700PF 100V BX 2-DIP

Package 2-DII

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CKR22BX472KM Specifications

Manufacturer Part Number CKR22BX472KM Manufacturer AVX Corporation Category Capacitors Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style - Report errors?		
Category Capacitors Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Manufacturer Part Number	CKR22BX472KM
Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Manufacturer	AVX Corporation
Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Category	Capacitors
Series Military, MIL-PRF-39014, CKR22 Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -		Ceramic Capacitors
Capacitance 4700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Package	2-DIP
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Series	Military, MIL-PRF-39014, CKR22
Voltage - Rated100VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.175" (4.45mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Capacitance	4700pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.175" (4.45mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Voltage - Rated	100V
Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Temperature Coefficient	BX
Ratings - General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style - General Purpose (General Purpose) - General Purpose (Mexicology) Through Hole (1%) - O.260" L x 0.092" W (6.60mm x 2.34mm) - O.325" (8.25mm) - O.325" (8.25mm)	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style	Features	Military
Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Ratings	-
Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Applications	General Purpose
Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Failure Rate	M (1%)
Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Package / Case	2-DIP
Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Size / Dimension	0.260" L x 0.092" W (6.60mm x 2.34mm)
Lead Spacing 0.325" (8.25mm) Lead Style -	Height - Seated (Max)	0.175" (4.45mm)
Lead Style -	Thickness (Max)	-
	Lead Spacing	0.325" (8.25mm)
Report errors?	Lead Style	-
		Report errors?

CKR22BX472KM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CKR22BX472KM Payment Methods



















CKR22BX472KM Shipping Methods













If you have any question about CKR22BX472KM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com