



#### **CKR22BX681KR Information**



For Reference Only

Part Number CKR22BX681KR
Manufacturer AVX Corporation
Category Capacitors

Capacitors
Ceramic Capacitors

**Description** CAP CER 680PF 200V RADIAL

Package 2-DIF

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CKR22BX681KR Specifications**

Manufacturer Part NumberCKR22BX681KRManufacturerAVX CorporationCategoryCapacitorsPackage2-DIPSeriesMilitary, MIL-PRF-39014, CKR22Capacitance680pFTolerance±10%Voltage - Rated200VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitary	
CategoryCapacitorsPackage2-DIPSeriesMilitary, MIL-PRF-39014, CKR22Capacitance $680pF$ Tolerance $\pm 10\%$ Voltage - Rated $200V$ Temperature CoefficientBXOperating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
$\begin{array}{cccc} & & & & & & & \\ & & & & & & \\ & & & & $	
Package2-DIPSeriesMilitary, MIL-PRF-39014, CKR22Capacitance $680pF$ Tolerance $\pm 10\%$ Voltage - Rated $200V$ Temperature CoefficientBXOperating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Series Military, MIL-PRF-39014, CKR22  Capacitance $680pF$ Tolerance $\pm 10\%$ Voltage - Rated $200V$ Temperature Coefficient BX  Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	
Capacitance $680 pF$ Tolerance $\pm 10\%$ Voltage - Rated $200 V$ Temperature CoefficientBXOperating Temperature $-55 ^{\circ}C \sim 125 ^{\circ}C$	
Tolerance $\pm 10\%$ Voltage - Rated $200V$ Temperature Coefficient BX  Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Voltage - Rated $200V$ Temperature CoefficientBXOperating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Temperature Coefficient BX  Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
Features Military	
Ratings -	
Applications General Purpose	
Failure Rate R (0.01%)	
Mounting Type Through Hole	
Package / Case 2-DIP	
Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm)	
Height - Seated (Max) 0.175" (4.45mm)	
Thickness (Max)	
Lead Spacing 0.325" (8.25mm)	
Lead Style -	
Report	

#### CKR22BX681KR Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CKR22BX681KR Payment Methods**





















## **CKR22BX681KR Shipping Methods**













If you have any question about CKR22BX681KR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com