



CKR22CG101KM Information

Heisener.com

Part NumberCKR22CG101KMManufacturerAVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 100PF 200V NP0 2-DIP

Package 2-DIF

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CKR22CG101KM Specifications

Manufacturer Part Number CKR22CG101KM Manufacturer AVX Corporation Category Capacitors Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 100pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -		
Category Capacitors Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 100pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Manufacturer Part Number	CKR22CG101KM
Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 100pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Manufacturer	AVX Corporation
Package 2-DIP Series Military, MIL-PRF-39014, CKR22 Capacitance 100pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Category	Capacitors
Series Military, MIL-PRF-39014, CKR22 Capacitance 100pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -		Ceramic Capacitors
Capacitance 100pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Package	2-DIP
Tolerance ±10% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Series	Military, MIL-PRF-39014, CKR22
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.175" (4.45mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Capacitance	100pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style - Coefficient COG, NP0 Co	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.175" (4.45mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Voltage - Rated	200V
FeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.175" (4.45mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style - General Purpose (General Purpose) - General Purpose (Mexicology) Through Hole (1%) - Comparison (1%) - C	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style	Features	Military
Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Ratings	-
Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Applications	General Purpose
Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Failure Rate	M (1%)
Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) 0.175" (4.45mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Package / Case	2-DIP
Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Size / Dimension	0.260" L x 0.092" W (6.60mm x 2.34mm)
Lead Spacing 0.325" (8.25mm) Lead Style -	Height - Seated (Max)	0.175" (4.45mm)
Lead Style -	Thickness (Max)	-
	Lead Spacing	0.325" (8.25mm)
Report errors?	Lead Style	-
		Report errors?

CKR22CG101KM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CKR22CG101KM Payment Methods



















CKR22CG101KM Shipping Methods













If you have any question about CKR22CG101KM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com