



CKR23CG272KM Information

Heisener.com

Part Number CKR23CG272KM Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 2700PF 100V NP0 2-DIP

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CKR23CG272KM Specifications

Manufacturer Part Number CKR23CG272KM Manufacturer AVX Corporation Category Capacitors Package 2-DIP Series Military, MIL-PRF-39014, CKR23 Capacitance 2700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -		
Category Capacitors Package 2-DIP Series Military, MIL-PRF-39014, CKR23 Capacitance 2700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Manufacturer Part Number	CKR23CG272KM
Package 2-DIP Series Military, MIL-PRF-39014, CKR23 Capacitance 2700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Manufacturer	AVX Corporation
Package 2-DIP Series Military, MIL-PRF-39014, CKR23 Capacitance 2700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Category	Capacitors
Series Military, MIL-PRF-39014, CKR23 Capacitance 2700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -		Ceramic Capacitors
Capacitance 2700pF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Package	2-DIP
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Series	Military, MIL-PRF-39014, CKR23
Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.195" (4.95mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Capacitance	2700pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style - Coefficient COG, NP0 Co	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.195" (4.95mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Voltage - Rated	100V
FeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateM (1%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.195" (4.95mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style - General Purpose (General Purpose) - General Purpose (Max) (1%) M (1%) Lead Style - General Purpose (General Purpose) - Applications (Max) (1%) - Comparison (Max) (1%) -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style	Features	Military
Failure Rate M (1%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Ratings	-
Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Applications	General Purpose
Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Failure Rate	M (1%)
Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style -	Package / Case	2-DIP
Thickness (Max) Lead Spacing 0.325" (8.25mm) Lead Style -	Size / Dimension	0.260" L x 0.092" W (6.60mm x 2.34mm)
Lead Spacing 0.325" (8.25mm) Lead Style -	Height - Seated (Max)	0.195" (4.95mm)
Lead Style -	Thickness (Max)	-
	Lead Spacing	0.325" (8.25mm)
Report errors?	Lead Style	-
		Report errors?

CKR23CG272KM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CKR23CG272KM Payment Methods



















CKR23CG272KM Shipping Methods













If you have any question about CKR23CG272KM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com