

CKR23CG472KR-LL

CKR23CG472KR-LL Information

Heisener.com

Part Number CKR23CG472KR-LL Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 4700PF 50V RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CKR23CG472KR-LL Specifications

Manufacturer Part NumberCKR23CG472KR-LLManufacturerAVX CorporationCategoryCapacitorsPackage2-DIPSeriesMilitary, MIL-PRF-39014, CKR23Capacitance4700pFTolerance±10%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeThrough HolePackage / Case2-DIP		
Category Capacitors Package 2-DIP Series Military, MIL-PRF-39014, CKR23 Capacitance 4700pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Manufacturer Part Number	CKR23CG472KR-LL
Package2-DIPSeriesMilitary, MIL-PRF-39014, CKR23Capacitance4700pFTolerance±10%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeThrough HolePackage / Case2-DIP	Manufacturer	AVX Corporation
Package 2-DIP Series Military, MIL-PRF-39014, CKR23 Capacitance 4700pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Category	Capacitors
Series Military, MIL-PRF-39014, CKR23 Capacitance 4700pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP		Ceramic Capacitors
Capacitance $4700pF$ Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature Coefficient $C0G, NP0$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%) Mounting TypeThrough HolePackage / Case2-DIP	Package	2-DIP
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Series	Military, MIL-PRF-39014, CKR23
Voltage - Rated Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Package / Case 50V COG, NPO -55°C ~ 125°C Military Ailitary Frailure Rate R (0.01%) Through Hole Package / Case 2-DIP	Capacitance	4700pF
Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Voltage - Rated	50V
Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Temperature Coefficient	C0G, NP0
Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Features	Military
Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP	Ratings	-
Mounting Type Through Hole Package / Case 2-DIP	Applications	General Purpose
Package / Case 2-DIP	Failure Rate	R (0.01%)
	Mounting Type	Through Hole
	Package / Case	2-DIP
Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm)	Size / Dimension	0.260" L x 0.092" W (6.60mm x 2.34mm)
Height - Seated (Max) 0.195" (4.95mm)	Height - Seated (Max)	0.195" (4.95mm)
Thickness (Max) -	Thickness (Max)	-
Lead Spacing 0.325" (8.25mm)	Lead Spacing	0.325" (8.25mm)
Lead Style -	Lead Style	-
Report errors		Report errors?

CKR23CG472KR-LL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CKR23CG472KR-LL Payment Methods





















CKR23CG472KR-LL Shipping Methods













If you have any question about CKR23CG472KR-LL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com