

# CKR23CG681KR-LL

### CKR23CG681KR-LL Information

Heisener.com

Part Number CKR23CG681KR-LL
Manufacturer AVX Corporation

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 680PF 200V RADIAL

Package 2-DIF

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CKR23CG681KR-LL Specifications**

Manufacturer Part Number         CKR23CG681KR-LL           Manufacturer         AVX Corporation           Category         Capacitors           Package         2-DIP           Series         Military, MIL-PRF-39014, CKR23           Capacitance         680pF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.092" W (6.60mm x 2.34mm)           Height - Seated (Max)         0.195" (4.95mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -		
Category         Capacitors           Package         2-DIP           Series         Military, MIL-PRF-39014, CKR23           Capacitance         680pF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         COG, NP0           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.092" W (6.60mm x 2.34mm)           Height - Seated (Max)         0.195" (4.95mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Manufacturer Part Number	CKR23CG681KR-LL
Package         2-DIP           Series         Military, MIL-PRF-39014, CKR23           Capacitance         680pF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.092" W (6.60mm x 2.34mm)           Height - Seated (Max)         0.195" (4.95mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Manufacturer	AVX Corporation
Package         2-DIP           Series         Military, MIL-PRF-39014, CKR23           Capacitance         680pF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.092" W (6.60mm x 2.34mm)           Height - Seated (Max)         0.195" (4.95mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Category	Capacitors
Series         Military, MIL-PRF-39014, CKR23           Capacitance         680pF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.092" W (6.60mm x 2.34mm)           Height - Seated (Max)         0.195" (4.95mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -		Ceramic Capacitors
Capacitance         680pF           Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.092" W (6.60mm x 2.34mm)           Height - Seated (Max)         0.195" (4.95mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Package	2-DIP
Tolerance         ±10%           Voltage - Rated         200V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Military           Ratings         -           Applications         General Purpose           Failure Rate         R (0.01%)           Mounting Type         Through Hole           Package / Case         2-DIP           Size / Dimension         0.260" L x 0.092" W (6.60mm x 2.34mm)           Height - Seated (Max)         0.195" (4.95mm)           Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Series	Military, MIL-PRF-39014, CKR23
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.195" (4.95mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Capacitance	680pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style - COG, NPO  Octor 125°C  Military  General Purpose General Purpose (Analy)  Con 125°C  Military  General Purpose (Analy)  Con 125°C  Military  Military  Applications  Octor 125°C  Octor 125°C  Military  Octor 125°C  Military  Octor 125°C  Military  Octor 125°C  Military  Octor 125°C  Octor 125	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.195" (4.95mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Voltage - Rated	200V
FeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeThrough HolePackage / Case2-DIPSize / Dimension0.260" L x 0.092" W (6.60mm x 2.34mm)Height - Seated (Max)0.195" (4.95mm)Thickness (Max)-Lead Spacing0.325" (8.25mm)Lead Style-	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style - General Purpose (General Purpose)  - General Purpose (R (0.01%)  R (0.01%)  - Output (	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case 2-DIP Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm) Height - Seated (Max) 0.195" (4.95mm) Thickness (Max) - Lead Spacing 0.325" (8.25mm) Lead Style	Features	Military
Failure Rate R (0.01%)  Mounting Type Through Hole  Package / Case 2-DIP  Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm)  Height - Seated (Max) 0.195" (4.95mm)  Thickness (Max) -  Lead Spacing 0.325" (8.25mm)  Lead Style -	Ratings	-
Mounting Type Through Hole  Package / Case 2-DIP  Size / Dimension 0.260" L x 0.092" W (6.60mm x 2.34mm)  Height - Seated (Max) 0.195" (4.95mm)  Thickness (Max) -  Lead Spacing 0.325" (8.25mm)  Lead Style -	Applications	General Purpose
Package / Case       2-DIP         Size / Dimension       0.260" L x 0.092" W (6.60mm x 2.34mm)         Height - Seated (Max)       0.195" (4.95mm)         Thickness (Max)       -         Lead Spacing       0.325" (8.25mm)         Lead Style       -	Failure Rate	R (0.01%)
Size / Dimension       0.260" L x 0.092" W (6.60mm x 2.34mm)         Height - Seated (Max)       0.195" (4.95mm)         Thickness (Max)       -         Lead Spacing       0.325" (8.25mm)         Lead Style       -	Mounting Type	Through Hole
Height - Seated (Max)       0.195" (4.95mm)         Thickness (Max)       -         Lead Spacing       0.325" (8.25mm)         Lead Style       -	Package / Case	2-DIP
Thickness (Max)         -           Lead Spacing         0.325" (8.25mm)           Lead Style         -	Size / Dimension	0.260" L x 0.092" W (6.60mm x 2.34mm)
Lead Spacing 0.325" (8.25mm)  Lead Style -	Height - Seated (Max)	0.195" (4.95mm)
Lead Style -	Thickness (Max)	-
	Lead Spacing	0.325" (8.25mm)
Report errors?	Lead Style	-
		Report errors?

#### **CKR23CG681KR-LL Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CKR23CG681KR-LL Payment Methods**



















# CKR23CG681KR-LL Shipping Methods













If you have any question about CKR23CG681KR-LL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com