

CL21C220JDCNCNC

CL21C220JDCNCNC Information

	Part Number	CL21C220JDCNCNC
ener.com		
	Manufacturer	Samsung
	Category	Capacitors
	8.	Ceramic Capacitors
	Description	CAP CER 22PF 200V COG/NP0 0805
	Package	0805 (2012 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

CL21C220JDCNCNC Specifications

ManufacturerSamsungCategoryCapacitorsPackage0805 (2012 Metric)SeriesCLCapacitance22pFYoltage - Rated200VToleranceCOG, NPOOperating Temperature Coefficient-55°C ~ 125°CPattings-55°C ~ 125°CRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.070° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Height - Seated (Max)- <t< th=""><th></th><th></th></t<>			
CategoryCapacitorsPackage0805 (2012 Metric)SeriesCLCapacitance22pFTolerance±5%Voltage - Rated200VOperating Temperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0.007" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Style-Lead Style-	Manufacturer Part Number	CL21C220JDCNCNC	
Ceramic CapacitorsPackage0805 (2012 Metric)SeriesCLCapacitance22pFTolerance±5%Voltage - Rated200VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.037" (0.95mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Style-	Manufacturer	Samsung	
Package0805 (2012 Metric)SeriesCLCapacitance22pFTolerance±5%Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSuface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style-	Category	Capacitors	
SeriesCLCapacitance22pFTolerance±5%Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.037" (0.45mm)Height - Seated (Max)-Lead Spacing-Lead Style-		Ceramic Capacitors	
Capacitance22pFTolerance±5%Voltage - Rated200VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style-	Package	0805 (2012 Metric)	
Tolerance±%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.037" (0.95mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Series	CL	
Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-5°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Lead Spacing0.037" (0.95mm)Lead Spacing-Kead Style-	Capacitance	22pF	
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Height Seated (Max)-Construction-State Spacing-State Spacing-Sta	Tolerance	±5%	
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Height - Seated (Max)-Stare Max-Stare	Voltage - Rated	200V	
Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Height Seated (Max)-Control-Cont	Temperature Coefficient	C0G, NP0	
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)-Star (Max)	Operating Temperature	-55°C ~ 125°C	
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style-	Features	-	
Failure Rate-Failure RateSurface Mount, MLCCMounting Type0805 (2012 Metric)Package / Case0.079" L x 0.049" W (2.00mm x 1.25mm)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style-	Ratings	-	
Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style-	Applications	General Purpose	
Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.95mm) Lead Spacing - Lead Style -	Failure Rate	-	
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.95mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC	
Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)	
Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style-	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)	
Lead Spacing-Lead Style-	Height - Seated (Max)	-	
Lead Style -	Thickness (Max)	0.037" (0.95mm)	
•	Lead Spacing	-	
Report errors?	Lead Style	-	
		Report errors?	

CL21C220JDCNCNC Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CL21C220JDCNCNC Payment Methods



If you have any question about CL21C220JDCNCNC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com