

CL21C221JDCNNNC

CL21C221JDCNNNC Information

| rener.com | Part Number Manufacturer Category Description Package | CL21C221JDCNNNC Samsung Capacitors Ceramic Capacitors CAP CER 220PF 200V C0G/NP0 0805 0805 (2012 Metric) For the pricing/inventory/lead time, please contact | |
|--------------------|---|--|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CL21C221JDCNNNC Specifications

| ManufacturerSamsungCategoryCapacitorsPackage8005 (2012 Metric)SeriesCLCapacitance220pFColaractance200VVoltage - Rated200VOperating Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.07°" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Tickness (Max)0.037" (0.95mm)Lead Spacing- | - | |
|---|--------------------------|---------------------------------------|
| Category Capacitors Package 0805 (2012 Metric) Series CL Capacitance 220pF Tolerance ±5% Voltage - Rated 200V Operating Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Sufface Mount, MLCC Package / Case 0.007° L x 0.049° W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.95mm) Lead Spacing - | Manufacturer Part Number | CL21C221JDCNNNC |
| Ceramic CapacitorsPackage0805 (2012 Metric)SeriesCLCapacitance220pFTolerance±5%Voltage - Rated200VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.037" (0.95mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style- | Manufacturer | Samsung |
| Package0805 (2012 Metric)SeriesCLCapacitance220pFTolerance±5%Voltage - Rated200VTomperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSuface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Category | Capacitors |
| SeriesCLCapacitance220pFTolerance±5%Voltage - Rated200VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | | Ceramic Capacitors |
| Capacitance220pFTolerance±5%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Nounting Type0805 (2012 Metric)Size / Dimension0.037" (0.95mm)Height - Seated (Max)-Lead Spacing-Lead Style-Style-Lead Style- | Package | 0805 (2012 Metric) |
| Tolerance±5%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Style-Lead Style- | Series | CL |
| Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Capacitance | 220pF |
| Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Tolerance | ±5% |
| Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Voltage - Rated | 200V |
| Features-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Temperature Coefficient | C0G, NP0 |
| Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)- </td <td>Operating Temperature</td> <td>-55°C ~ 125°C</td> | Operating Temperature | -55°C ~ 125°C |
| ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Features | - |
| Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Ratings | - |
| Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.95mm) Lead Spacing - Lead Style - | Applications | General Purpose |
| Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.95mm) Lead Spacing - Lead Style - | Failure Rate | - |
| Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.95mm) Lead Spacing - Lead Style - | Mounting Type | Surface Mount, MLCC |
| Height - Seated (Max)-Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Package / Case | 0805 (2012 Metric) |
| Thickness (Max)0.037" (0.95mm)Lead Spacing-Lead Style- | Size / Dimension | 0.079" L x 0.049" W (2.00mm x 1.25mm) |
| Lead Spacing - Lead Style - | Height - Seated (Max) | - |
| Lead Style - | Thickness (Max) | 0.037" (0.95mm) |
| | Lead Spacing | - |
| Report errors? | Lead Style | - |
| | | Report errors? |

CL21C221JDCNNNC Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CL21C221JDCNNNC Payment Methods





If you have any question about CL21C221JDCNNNC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com