

# CL21C390JBANNNC

## **CL21C390JBANNNC Information**

eisener.com	Part Number Manufacturer Category Description Package	CL21C390JBANNNC Samsung Capacitors Ceramic Capacitors CAP CER 39PF 50V C0G/NP0 0805 0805 (2012 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **CL21C390JBANNNC** Specifications

Manufacturer Part Number CL21C390JBANNNC   Manufacturer Samsung   Category Capacitors   Caranic Capacitors Ceranic Capacitors   Package 0805 (2012 Metric)   Series CL   Capacitance 39pF   Tolerance ±5%   Voltage - Rated 50% OK   Yoltage - Rated COG, NPO   Operating Temperature 05% C × 125°C   Pactures -   Applications General Purpose   Faitures Rate -   Applications General Purpose   Faiture Rate -   Mounting Type Surface Mount, MLCC   Package / Case 005% (2012 Metric)   Size / Dimension 0.030° (0.75mm)   Height - Seated (Max) -   Fickness (Max) -   Lead Spacing -		
CategoryCaramic CapacitorsPackage0805 (2012 Metric)Series0805 (2012 Metric)Capacitance39pFColarance±5%Yoltage - Rated50VTomperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0.07° L x 0.049° W (2.00mm x 1.25mm)Fickness (Max)0.30° (0.75mm)Lead Spacing-Lead Style-Lead Style-Lead Style-Lead Style-	Manufacturer Part Number	CL21C390JBANNNC
Ceranic CapacitorsPackage0805 (2012 Metric)SeriesCLCapacitance39pFTolerance±5%Voltage - Rated50VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting Type0805 (2012 Metric)Size / Dimension0.030° (0.75mm)Height - Seated (Max)-Lead Spacing-Starley	Manufacturer	Samsung
Package0805 (2012 Metric)SeriesCLCapacitance39pFTolerance±5%Voltage Rated50VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Noutring TypeSufface Mount, MLCCStack J Chase.0079° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max).030° (0.75mm)Lead Spacing.Lead Style.	Category	Capacitors
SeriesCLCapacitance39pFTolerance±5%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Lead Spacing-Lead Style-Style<		Ceramic Capacitors
Capacitance39pFTolerance±5%Voltage - Rated50VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.079° L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.30° (0.75mm)Lead Spacing-Lead Style-State Style-State Style-State Style-State Style-State Style-State Style-State Style-St	Package	0805 (2012 Metric)
Tolerance±5%Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.030" (0.75mm)Height - Seated (Max)-Lead Spacing0.303" (0.75mm)Lead Style-State Style-	Series	CL
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFaiture Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.079" L x 0.049" W (2.00mm x 1.25mm)Size / Dimension-Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-	Capacitance	39pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-State Style-	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)-Start - Seated (Max)-Height - Seated (Max)- <td>Operating Temperature</td> <td>-55°C ~ 125°C</td>	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case 0805 (2012 Metric)   Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm)   Height - Seated (Max) -   Thickness (Max) 0.030" (0.75mm)   Lead Spacing -   Lead Style -	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm)   Height - Seated (Max) -   Thickness (Max) 0.030" (0.75mm)   Lead Spacing -   Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)
Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.030" (0.75mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

## **CL21C390JBANNNC** Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **CL21C390JBANNNC Payment Methods**





If you have any question about CL21C390JBANNNC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com