

CL21F473ZBANNNC

CL21F473ZBANNNC Information

eisener.com	Part Number Manufacturer Category Description Package	CL21F473ZBANNNC Samsung Capacitors Ceramic Capacitors CAP CER 0.047UF 50V Y5V 0805 0805 (2012 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CL21F473ZBANNNC Specifications

ManufacturerSamsungCacacitorsCeramic CapacitorsPackage8005 (2012 Metric)SeriesCLCapacitance0.047µFColtage - Rated50VVoltage - Rated50VOperating Temperature Coefficient95°C ~ 85°CPactangs-30°C ~ 85°CRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.00°T x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Hickness (Max)0.30° (0.75mm)Lead Spacing-Lead Spacing-Startings-Startings-Startings-Startings0.030° (0.75mm)Startings- </th <th></th> <th></th>		
CategoryCapacitorsPackage0805 (2012 Metric)Package0805 (2012 Metric)SeriesCLCapacitance0.047µFTolerance-20%, +80%Voltage - Rated50VOperating Temperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSuf Goult Metric)Package / Case0.0070 °L x 0.049° W (2.00mm x 1.25mm)Height - Seated (Max)-Height - Seated (Max)-Thickness (Max)0.030° (0.75mm)Lead Spacing-Lead Style-	Manufacturer Part Number	CL21F473ZBANNNC
Ceranic CapacitorsPackage0805 (2012 Metric)SeriesCLCapacitance0.047µFTolerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.030" (0.75mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Manufacturer	Samsung
Package0805 (2012 Metric)SeriesCLCapacitance0.047µFTolerance-20%, +80%Voltage - Rated50VTomperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeS05 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Height - Seated (Max)-Height Seated (Max)-Lead Spacing-Lead Style-	Category	Capacitors
SeriesCLCapacitance0.047µFTolerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance0.047µFTolerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.30" (0.75mm)Lead Spacing-Agstige-Stafe Style-Style	Package	0805 (2012 Metric)
Tolerance-20%, +80%Voltage - Rated50VTemperature CoefficientV5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-0.30°" (L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Hickness (Max)0.030" (0.75mm)Lead Style-Head Style-	Series	CL
Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension-Height - Seated (Max)-Lead Spacing0.030" (0.75mm)Lead Style-	Capacitance	0.047µF
Temperature Coefficient Y5V (F) Operating Temperature -30°C ~ 85°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.030" (0.75mm) Lead Spacing -	Tolerance	-20%, +80%
Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Height - Seated (Max)-Stare Spacing-Stare Spacing	Voltage - Rated	50V
Features-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Temperature Coefficient	Y5V (F)
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Operating Temperature	-30°C ~ 85°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Features	-
Failure Rate-Failure RateSurface Mount, MLCCMounting Type0805 (2012 Metric)Package / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.030" (0.75mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Package / Case	0805 (2012 Metric)
Thickness (Max)0.030" (0.75mm)Lead Spacing-Lead Style-	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.030" (0.75mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

CL21F473ZBANNNC Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CL21F473ZBANNNC Payment Methods





If you have any question about CL21F473ZBANNNC, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com