

CLM-107-02-F-D-A

CLM-107-02-F-D-A Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CLM-107-02-F-D-A Specifications

Manufacturer Part Number CLM-107-02-F-D-A Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series CLM Connector Type Receptacle Contact Type Receptacle Sories Goard to Board Number of Positions All Number of Positions Loaded All Number of Rows 2 Row Spacing - Mating 0.039" (1.00mm) Mounting Type Surface Mount Yearde Mounting Type Surface Mount Contact Finish - Mating Gold Contact Finish - Mating Gold Contact Finish Thickness - Mating Juin (0.08µm) Insulation Color Black Insulation Fleight 0.084" (2.14mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C		
CategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLMConnector TypeReceptacleContact TypeBoard to BoardStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0:039" (1.00mm)Number of Rows0:039" (1.00mm)Number of Rows0:04"Number of R	Manufacturer Part Number	CLM-107-02-F-D-A
Icataguar Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountMounting TypeSurface MountFerminationSolderForsteining TypeSurface MountContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Songer TypeSinger Colores Colo	Manufacturer	Samtec Inc.
Package-SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects
SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSolderFerminationSolderFortar Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderContact Finish - MatingGoldContact Finish Thickness - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Sor C - 125°C-	Package	-
Contact TypeFenale SocketStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Series	CLM
StyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Connector Type	Receptacle
Number of Positions 14 Number of Positions Loaded All Pitch - Mating 0.039" (1.00mm) Number of Rows 2 Row Spacing - Mating 0.039" (1.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Insulation Color Black Insulation Height 0.084" (2.14mm) Contact Length - Post - Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJiin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSurface MountFastening TypePosh-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.084" (2.14mm)Contact Length - Post-Sorfact Contact Finish - Sorfact Contact Finish0.55°C ~ 125°C	Number of Positions	14
Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Pitch - Mating	0.039" (1.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.039" (1.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.084" (2.14mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	3μin (0.08μm)
Contact Length - Post-Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.084" (2.14mm)
	Contact Length - Post	-
Material Flammability Rating LII 94 V_0	Operating Temperature	-55°C ~ 125°C
Viachar Flammaonity Rating	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Guide
	Report errors?

CLM-107-02-F-D-A Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CLM-107-02-F-D-A Payment Methods



If you have any question about CLM-107-02-F-D-A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com