

# CLM-111-02-L-D-BE-A

## CLM-111-02-L-D-BE-A Information



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# CLM-111-02-L-D-BE-A Specifications

Manufacturer Part NumberCLM-111-02-L-D-BE-AManufacturerSantec Inc.CategoryConnectors, InterconnectsPackage-Package-SeriesCLMConnector TypeRectangular Connectors - Headers, Receptacles, Female SocketsContact TypeReceptacle, Bottom EntryContact TypeBoard to BoardStyleBoard to BoardNumber of Positions22Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFerminationSolderFastening TypePosh-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-		
Category Connectors. Interconnects   Rectangular Connectors - Headers, Receptacles, Female Sockets   Package -   Series CLM   Connector Type Receptacle, Bottom Entry   Contact Type Female Socket   Style Board to Board   Number of Positions 22   Number of Positions Loaded All   Pitch - Mating 0.039" (1.00mm)   Number of Rows 2   Row Spacing - Mating 0.039" (1.00mm)   Mounting Type Surdace Mount   Fersination Solder   Formination Solder   Contact Finish - Mating Gold   Contact Finish - Mating Gold   Insulation Color Black   Insulation Finish - Mating Injun (0.25µm)   Insulation Height 0.084" (2.14mm)	Manufacturer Part Number	CLM-111-02-L-D-BE-A
Icetangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLMConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions22Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Number of Rows0.039" (1.00mm)Pitch - Mating0.039" (1.00mm)Mounting TypeSolderForminationSolderForting TypeGoldContact Finish - MatingGoldContact Finish - MatingBiakInsulation ColorBiakInsulation Finish0.084" (2.14mm)Contact Finish - Post-	Manufacturer	Samtec Inc.
Package-SeriesCLMConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions22Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFerminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingIopin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Category	Connectors, Interconnects
SeriesCLMConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions22Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFastening TypeSurface MountContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions22Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFastening TypeSulface MountContact Finish - MatingGoldContact Finish Finkeness - MatingIlouin (0.55µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions22Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Series	CLM
StyleBoard to BoardStyleBoard to BoardNumber of Positions22Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Connector Type	Receptacle, Bottom Entry
Number of Positions22Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorJinin (0.25µm)Insulation Height0.084" (2.14mm)Contact Length - Post-	Style	Board to Board
Pitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting Type0.039" (1.00mm)TerminationSurface MountFastening TypePosh-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Number of Positions	22
Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Number of Positions Loaded	All
Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Pitch - Mating	0.039" (1.00mm)
Nounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Row Spacing - Mating	0.039" (1.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Termination	Solder
Contact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Contact Finish - Mating	Gold
Insulation Height0.084" (2.14mm)Contact Length - Post-	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post -	Insulation Color	Black
	Insulation Height	0.084" (2.14mm)
	Contact Length - Post	-
Operating Temperature -55°C ~ 125°C	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Guide
	Report errors?

## CLM-111-02-L-D-BE-A Guarantees



#### **Quality Guarantees**


We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# CLM-111-02-L-D-BE-A Payment Methods



If you have any question about CLM-111-02-L-D-BE-A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com