

CLM-132-02-LM-D-PA-TR

CLM-132-02-LM-D-PA-TR Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CLM-132-02-LM-D-PA-TR Specifications

Manufacturer Part NumberCLM-132-02-LM-D-PA-TRManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFerninationSolderFastening TypePush-Pull		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions Loaded0.039" (1.00mm)Pitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - MatingSurface MountMounting TypeSurface MountFastening TypePush-Pull	Manufacturer Part Number	CLM-132-02-LM-D-PA-TR
Hectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedNog9" (1.00mm)Pitch - Mating0.39" (1.00mm)Number of Rows2Row Spacing - MatingSurface MountMounting TypeSolderFastening TypePush-Pull	Manufacturer	Samtec Inc.
Package-SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFastening TypePush-Pull	Category	Connectors, Interconnects
SeriesCLMConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFastening TypePush-Pull		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountFastening TypePush-Pull	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Series	CLM
StyleBoard to BoardNumber of Positions64Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Connector Type	Receptacle
Number of Positions64Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Style	Board to Board
Pitch - Mating0.039" (1.00mm)Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Number of Positions	64
Number of Rows2Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Number of Positions Loaded	All
Row Spacing - Mating0.039" (1.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Pitch - Mating	0.039" (1.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-Pull	Number of Rows	2
Termination Solder Fastening Type Push-Pull	Row Spacing - Mating	0.039" (1.00mm)
Fastening Type Push-Pull	Mounting Type	Surface Mount
	Termination	Solder
	Fastening Type	Push-Pull
Contact Finish - Mating Gold	Contact Finish - Mating	Gold
Contact Finish Thickness - Mating 10µin (0.25µm)	Contact Finish Thickness - Mating	10μin (0.25μm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.084" (2.14mm)	Insulation Height	0.084" (2.14mm)
Contact Length - Post -	Contact Length - Post	-
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Pick and Place

Report errors?

DISCOVER

CLM-132-02-LM-D-PA-TR Guarantees **Quality Guarantees** We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition. **Service Guarantees** SFRV We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers. CLM-132-02-LM-D-PA-TR Payment Methods WIRE transfer **PayPal** S MoneyGram Alipay VISA CLM-132-02-LM-D-PA-TR Shipping Methods **ZHL_ FedEx. 10 TRT**

If you have any question about CLM-132-02-LM-D-PA-TR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com