

CLP-150-02-G-D

CLP-150-02-G-D Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CLP-150-02-G-D Specifications

Manufacturer Part NumberCLP-150-02-G-DManufacturerSamtee Inc.CategoryConnectors, InterconnectsPackage-SeriesCLPConnector TypeReceptacles, Female SocketsConnector TypeReceptacleConnector TypeSeriel SocketStyleBoard BoardNumber of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountMounting TypeSurface MountFrankaning0.050" (1.27mm)Mounting TypeSurface MountContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingUpin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-Contact Finish Thickness - Mating-Insulation Height0.084" (2.14mm)Contact Finish - Mating-Insulation Height-Insulation Height <t< th=""><th></th><th></th></t<>				
CategoryConnectors InterconnectsPackage-SeriesCLPConnector TypeRecptacleConnector TypeRecptacleContact TypeBard to BoardStyleSord to BoardNumber of PositionsOloPackage-Number of PositionsOloStyleSord 'L27mm'Number of Rows2Row Spacing - MatingSolo' (1.27mm)Number of RowsSolo' (1.27mm)Number of RowsSolo' (1.27mm)Stating TypeSolo' (1.27mm)Stating TypeSolo' (1.27mm)ForninationSolo' (1.27mm)Contact Finish - MatingSolo' (1.27mm)Stating TypeSolo' (1.2	Manufacturer Part Number	CLP-150-02-G-D		
NumberRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLPConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions100Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountPriminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIlpuin (0.52µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Manufacturer	Samtec Inc.		
Package-SeriesCLPConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions100Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish - MatingIoµin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Category	Connectors, Interconnects		
SeriesCLPConnector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions100Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountFastening TypeSurface MountContact Finish - MatingSolderContact Finish - MatingGoldInsulation ColorBlackInsulation Field0.054" (2.14mm)Contact Length - Post.		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions100Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingIopin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Package	-		
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions100Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Series	CLP		
StyleBoard to BoardNumber of Positions100Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Connector Type	Receptacle		
Number of Positions100Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Contact Type	Female Socket		
Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Style	Board to Board		
Pitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting Type0.050" (1.27mm)TerminationSurface MountFastening TypeSolderFontact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Number of Positions	100		
Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Number of Positions Loaded	All		
Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Pitch - Mating	0.050" (1.27mm)		
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Number of Rows	2		
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Row Spacing - Mating	0.050" (1.27mm)		
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Mounting Type	Surface Mount		
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Termination	Solder		
Contact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height0.084" (2.14mm)Contact Length - Post-	Contact Finish - Mating	Gold		
Insulation Height0.084" (2.14mm)Contact Length - Post-	Contact Finish Thickness - Mating	10µin (0.25µm)		
Contact Length - Post -	Insulation Color	Black		
-	Insulation Height	0.084" (2.14mm)		
	Contact Length - Post	-		
Operating Temperature -55°C ~ 125°C	Operating Temperature	-55°C ~ 125°C		
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

CLP-150-02-G-D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CLP-150-02-G-D Payment Methods



If you have any question about CLP-150-02-G-D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com