



CLQ4D10NP-680NC Information

Heisener.com

Part Number CLQ4D10NP-680NC

Manufacturer Sumida America Components Inc.

Category Inductors, Coils, Chokes

Fixed Inductors

FIXED IND 68UH 240MA 1.9 OHM SMD **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CLQ4D10NP-680NC Specifications

Manufacturer Sumida America Components Inc. Category Inductors, Coils, Chokes Fixed Inductors Package 4-SMD Series CLQ4D10 Type - Material - Core - Inductance 68μH Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Features 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD Supplier Device Package -	Manufacturer Part Number	CLQ4D10NP-680NC
Package 4-SMD Series CLQ4D10 Type - Material - Core - Inductance 68μH Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Manufacturer	Sumida America Components Inc.
Package 4-SMD Series CLQ4D10 Type - Material - Core - Inductance 68µH Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Category	Inductors, Coils, Chokes
Series CLQ4D10 Type - Material - Core - Inductance 68μH Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD		Fixed Inductors
Type - Material - Core - Inductance 68µH Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Package	4-SMD
Material - Core - Inductance 68μH Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Series	CLQ4D10
Inductance 68µH Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Туре	-
Tolerance ±30% Current Rating 240mA Current - Saturation - Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Material - Core	-
Current Rating Current - Saturation Shielding Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant Ratings - Operating Temperature Frequency - Test Frequency - Test Features Mounting Type Surface Mount Package / Case 240mA 240	Inductance	68μΗ
Current - Saturation - Shielding Shielded Shielded DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - CAMPACT - C	Tolerance	±30%
Shielding DC Resistance (DCR) 1.9 Ohm Max Q @ Freq - Frequency - Self Resonant - Ratings - Operating Temperature Frequency - Test Frequency - Test Foatures Mounting Type Surface Mount Package / Case Shielded 1.9 Ohm Max - 1.9 Ohm Max - 1.0 Ohm Max - 1.	Current Rating	240mA
DC Resistance (DCR) Q @ Freq Frequency - Self Resonant Ratings Operating Temperature Frequency - Test I00kHz Features Mounting Type Surface Mount Package / Case 1.9 Ohm Max 1.0 Ohm Max 1.	Current - Saturation	-
Q @ Freq-Frequency - Self Resonant-Ratings-Operating Temperature-Frequency - Test100kHzFeatures-Mounting TypeSurface MountPackage / Case4-SMD	Shielding	Shielded
Frequency - Self Resonant Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	DC Resistance (DCR)	1.9 Ohm Max
Ratings - Operating Temperature - Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Q @ Freq	-
Operating Temperature Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Frequency - Self Resonant	-
Frequency - Test 100kHz Features - Mounting Type Surface Mount Package / Case 4-SMD	Ratings	-
Features - Mounting Type Surface Mount Package / Case 4-SMD	Operating Temperature	-
Mounting Type Surface Mount Package / Case 4-SMD	Frequency - Test	100kHz
Package / Case 4-SMD	Features	-
-	Mounting Type	Surface Mount
Supplier Device Package -	Package / Case	4-SMD
	Supplier Device Package	-
Size / Dimension 0.213" L x 0.189" W (5.40mm x 4.80mm)	Size / Dimension	0.213" L x 0.189" W (5.40mm x 4.80mm)

Height - Seated (Max) 0.047" (1.20mm) Report errors?

CLQ4D10NP-680NC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CLQ4D10NP-680NC Payment Methods





















CLQ4D10NP-680NC Shipping Methods













If you have any question about CLQ4D10NP-680NC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com