

# CLT-109-02-L-D-BE-P-TR

#### CLT-109-02-L-D-BE-P-TR Information

Www.hatcherteen	Part Number Manufacturer	CLT-109-02-L-D-BE-P-TR Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	2MM SOCKET STRIPS	
	Package	-	国語愛感
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### CLT-109-02-L-D-BE-P-TR Specifications

Manufacturer Part NumberCLT-109-02-L-D-BE-P-TRManufacturerSamtee Inc.CategoryConnectors, InterconnectsPackage-SeriesCLTConnector TypeCCTContact TypeReceptacle, Bottom EntryContact TypeBoard to BoardStyleBoard to BoardNumber of Positions LoadedAllNumber of Rows2Rowspacing - Mating0079° (2.00mn)Number of Rows2Routing TypeSolderFrankationSolderStraten MatingSolderContact Finish - MatingGoldStraten TypeGoldStraten TypeSolderStraten Type<		
CategoryConnectors - Headers, Receptacles, Female SocketsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLTConnector TypeReceptacle, Bottom EntryContact TypeBoard to BoardStyleBoard to BoardNumber of PositionsAllNumber of Positions LoadedAllNumber of Rows2Row Spacing - MatingOrongr (2.00mn)Number of RowsSurface MountaNumber of RowsSurface MountaPreminationSolderForniationGoldContact Finish - MatingIopin (0.25µm)Insulation ColorBackInsulation Finish - MatingIopin (0.25µm)Insulation Finish - MatingIopin (0.2	Manufacturer Part Number	CLT-109-02-L-D-BE-P-TR
Headers, Receptacles, Female SocketsPackage-SeriesCLTConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPich - Mating0.079° (2.00mm)Number of Rows2Row Spacing - MatingSolderYouring TypeSurface MountYouring TypeSolderFeminationGoldContact Finish - MatingOug's (2.01mm)Contact Finish Thickness - MatingIojun (0.25µm)Insulation ColorBlackInsulation Height0.083° (2.10mm)Contact Length - Post-Sontar Length - Post-	Manufacturer	Samtec Inc.
Package-SeriesCLTConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
SeriesCLTConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountYenninationSolderForninationSolderContact Finish - MatingGoldContact Finish - MatingGoldSundion ColorBlackInsulation ColorBlackInsulation Height0.083" (2.10mm)Contact Fungt-Post-SolderSinger ColormanSundion Height0.58°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllNumber of Rows2Number of Rows0.079" (2.00mm)Number of Rows0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-SolderSinger ColorInsulation Height0.83" (2.10mm)Contact Finish Thotknes-SolderSinger ColorSolderSinger ColorSolder <td< td=""><td>Package</td><td>-</td></td<>	Package	-
Contact TypeFenale SocketStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating0.04Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Series	CLT
StyleBoard to BoardStyleBoard to BoardNumber of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Connector Type	Receptacle, Bottom Entry
Number of Positions18Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Solder 2000-Solder 2000-Solde	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJipin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSurface MountFastening TypePosh-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.083" (2.10mm)Contact Length - Post-Sperating Type-Solder- <td>Number of Positions</td> <td>18</td>	Number of Positions	18
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingI/uin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	10µin (0.25µm)
Contact Length - Post-Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.083" (2.10mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Pick and Place

Report errors?

## CLT-109-02-L-D-BE-P-TR Guarantees **Quality Guarantees** We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition. **Service Guarantees** SERVI We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers. CLT-109-02-L-D-BE-P-TR Payment Methods WIRE transfer Ҏ PayPal S MoneyGram Alipay UNION N/U DISCOVER VISA CLT-109-02-L-D-BE-P-TR Shipping Methods DHL\_ If you have any question about CLT-109-02-L-D-BE-P-TR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com