



CLT-128-02-G-D-BE-K Information



For Reference Only

Part Number CLT-128-02-G-D-BE-K

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description 2MM SOCKET STRIPS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CLT-128-02-G-D-BE-K Specifications

Manufacturer Part NumberCLT-128-02-G-D-BE-KManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesCLTConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series CLT Connector Type Receptacle, Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 56 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post - Contact Length - Po	Manufacturer Part Number	CLT-128-02-G-D-BE-K
Package-SeriesCLTConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-	Manufacturer	Samtec Inc.
Package - CLT Connector Type Receptacle, Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 56 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post	Category	Connectors, Interconnects
SeriesCLTConnector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle, Bottom Entry Contact Type Female Socket Style Board to Board Number of Positions 56 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 56 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post -	Series	CLT
Style Board to Board Number of Positions 56 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post -	Connector Type	Receptacle, Bottom Entry
Number of Positions Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post -	Style	Board to Board
Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Surface Mount Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post -	Number of Positions	56
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-	Pitch - Mating	0.079" (2.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post -	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.083" (2.10mm)Contact Length - Post-	Termination	Solder
Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post -	Fastening Type	Push-Pull
Insulation Color Black Insulation Height 0.083" (2.10mm) Contact Length - Post -	Contact Finish - Mating	Gold
Insulation Height 0.083" (2.10mm) Contact Length - Post -	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post -	Insulation Color	Black
·	Insulation Height	0.083" (2.10mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Length - Post	-
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold
Mated Stacking Heights	-
Ingress Protection	-
Features	Pick and Place
	Report errors?

CLT-128-02-G-D-BE-K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CLT-128-02-G-D-BE-K Payment Methods



















CLT-128-02-G-D-BE-K Shipping Methods













If you have any question about CLT-128-02-G-D-BE-K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com