



CMD264-UBD Information

www.harsener.a.m

For Reference Only

Part Number CMD264-UBD

Manufacturer Visual Communications Company - VCC

Category Optoelectronics

LED Indication - Discrete

Description LED BLUE DIFF 3MM ROUND T/H

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CMD264-UBD Specifications

Manufacturer CMD264-UBD Manufacturer Visual Communications Company - VCC Category Optoelectronics LED Indication - Discrete Package Radial Series - Color Blue Configuration - Lens Color Blue Lens Transparency Diffused Millicandela Rating 100mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 4.9V Current - Test 20mA Viewing Angle 45° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 430nm Features - Package / Case Radial Surplier Davice Package T. I.		
CategoryOptoelectronicsPackageRadialSeries-ColorBlueConfiguration-Lens ColorBlueLens TransparencyDiffusedMillicandela Rating100mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)4.9VCurrent - Test20mAViewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Manufacturer Part Number	CMD264-UBD
PackageRadialSeries-ColorBlueConfiguration-Lens ColorBlueLens TransparencyDiffusedMillicandela Rating100mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)4.9VCurrent - Test20mAViewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Manufacturer	Visual Communications Company - VCC
PackageRadialSeries-ColorBlueConfiguration-Lens ColorBlueLens TransparencyDiffusedMillicandela Rating100mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)4.9VCurrent - Test20mAViewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Category	Optoelectronics
Series - Color Blue Configuration - Lens Color Blue Diffused Diffused Millicandela Rating 100mcd Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 4.9V Current - Test 20mA Viewing Angle 45° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 430nm Features - Radial		LED Indication - Discrete
ColorBlueConfiguration-Lens ColorBlueLens TransparencyDiffusedMillicandela Rating100mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)4.9VCurrent - Test20mAViewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Package	Radial
Configuration-Lens ColorBlueLens TransparencyDiffusedMillicandela Rating100mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)4.9VCurrent - Test20mAViewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Series	-
Lens ColorBlueLens TransparencyDiffusedMillicandela Rating100mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)4.9VCurrent - Test20mAViewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Color	Blue
Lens TransparencyDiffusedMillicandela Rating100mcdLens Style/SizeRound with Domed Top, 3mm (T-1), 2.90mmVoltage - Forward (Vf) (Typ)4.9VCurrent - Test20mAViewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 4.9V Current - Test 20mA Viewing Angle 45° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 430nm Features - Package / Case Radial	Lens Color	Blue
Lens Style/Size Round with Domed Top, 3mm (T-1), 2.90mm Voltage - Forward (Vf) (Typ) 4.9V Current - Test 20mA Viewing Angle 45° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 430nm Features - Package / Case Radial	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ) 4.9V Current - Test 20mA Viewing Angle 45° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 430nm Features - Package / Case Radial	Millicandela Rating	100mcd
Current - Test 20mA Viewing Angle 45° Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 430nm Features - Package / Case Radial	Lens Style/Size	Round with Domed Top, 3mm (T-1), 2.90mm
Viewing Angle45°Mounting TypeThrough HoleWavelength - Dominant-Wavelength - Peak430nmFeatures-Package / CaseRadial	Voltage - Forward (Vf) (Typ)	4.9V
Mounting Type Through Hole Wavelength - Dominant - Wavelength - Peak 430nm Features - Package / Case Radial	Current - Test	20mA
Wavelength - Dominant - Wavelength - Peak 430nm Features - Package / Case Radial	Viewing Angle	45°
Wavelength - Peak 430nm Features - Package / Case Radial	Mounting Type	Through Hole
Features - Package / Case Radial	Wavelength - Dominant	-
Package / Case Radial	Wavelength - Peak	430nm
	Features	-
Supplier Davice Package T 1	Package / Case	Radial
Supplied Device I ackage 1-1	Supplier Device Package	T-1
Size / Dimension -	Size / Dimension	-
Height (Max) 4.50mm	Height (Max)	4.50mm
Report errors?		Report errors?

CMD264-UBD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CMD264-UBD Payment Methods





















CMD264-UBD Shipping Methods













If you have any question about CMD264-UBD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com