

CMDA2AY7D1S

CMDA2AY7D1S Information

Heisener.com	 CMDA2AY7D1S Visual Communications Company - VCC Optoelectronics LED Indication - Discrete LED GREEN DIFFUSED 1206 SMD 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CMDA2AY7D1S Specifications

Manufacturer Visual Communications Company - VCC Manufacturer Optoelectronics EED Indication - Discrete Package 1206 (3216 Metric) Series - Color Green Configuration - Lens Color White Lens Transparency Diffused Millicandela Rating 15mcd Voltage - Forward (Vf) (Typ) 2.2V Current - Test 20mA Viewing Angle 170° Mounting Type Surface Mount Wavelength - Poaka 570nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 1206 (3216 Metric) Size / Dimension 3.20mm L x 1.60mm W		
CategoryOptoelectronicsLED Indication - DiscretePackage1206 (3216 Metric)Series-ColorGreenConfiguration-Lens ColorWhiteLens TransparencyDiffusedMillicandela Rating15mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAWavelength - Dominant-Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Manufacturer Part Number	CMDA2AY7D1S
LED Indication - DiscretePackage1206 (3216 Metric)Series-ColorGreenConfiguration-Lens ColorWhiteLens TransparencyDiffusedMillicandela Rating15mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Vavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Surplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Manufacturer	Visual Communications Company - VCC
Package1206 (3216 Metric)Series-ColorGreenConfiguration-Lens ColorWhiteLens TansparencyDiffusedMillicandela Rating15mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAWouting TypeSurface MountWavelength - Dominant-Vavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Surplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.00mm	Category	Optoelectronics
Series-ColorGreenConfiguration-Lens ColorWhiteLens ColorDiffusedMillicandela Rating15mcdKlilicandela RatingRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Munting TypeSurface MountWavelength - Dominant-Features570nmPackage / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm		LED Indication - Discrete
ColorGreenConfiguration-Lens ColorWhiteLens ColorDiffusedMillicandela Rating15mcdKullicandela RatingRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAVoltage Angle170°Munting TypeSurface MountWavelength - Dominant-Features-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Package	1206 (3216 Metric)
Configuration-Lens ColorWhiteLens TransparencyDiffusedMillicandela Rating15mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Vavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Series	-
Lens ColorWhiteLens TransparencyDiffusedMillicandela Rating15mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Color	Green
Lens TransparencyDiffusedMillicandela Rating15mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Features-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension1.10mm	Configuration	-
Millicandela Rating15mcdLens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Features570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Lens Color	White
Lens Style/SizeRectangle with Flat Top, 2.00mm x 1.60mmVoltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Lens Transparency	Diffused
Voltage - Forward (Vf) (Typ)2.2VCurrent - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Millicandela Rating	15mcd
Current - Test20mAViewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Lens Style/Size	Rectangle with Flat Top, 2.00mm x 1.60mm
Viewing Angle170°Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package3.20mm L x 1.60mm WHeight (Max)1.10mm	Voltage - Forward (Vf) (Typ)	2.2V
Mounting TypeSurface MountWavelength - Dominant-Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Current - Test	20mA
Wavelength - Dominant-Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Viewing Angle	170°
Wavelength - Peak570nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Mounting Type	Surface Mount
Features-Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Wavelength - Dominant	-
Package / Case1206 (3216 Metric)Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Wavelength - Peak	570nm
Supplier Device Package1206 (3216 Metric)Size / Dimension3.20mm L x 1.60mm WHeight (Max)1.10mm	Features	-
Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.10mm	Package / Case	1206 (3216 Metric)
Height (Max) 1.10mm	Supplier Device Package	1206 (3216 Metric)
	Size / Dimension	3.20mm L x 1.60mm W
Report errors?	Height (Max)	1.10mm
		Report errors?

CMDA2AY7D1S Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CMDA2AY7D1S Payment Methods



CMDA2AY7D1S Shipping Methods



If you have any question about CMDA2AY7D1S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com