

CMF-SD35-10-2 Information



For Reference Only

Part Number CMF-SD35-10-2

Manufacturer Bourns Inc.

Category Circuit Protection
PTC Resettable Fuses

Description CPTC FUSE RESETTABLE

Package 4-SMD Cube

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CMF-SD35-10-2 Specifications

Manufacturer Part Number CMF-SD35-10-2 Manufacturer Bourns Inc. Category Circuit Protection Package 4-SMD Cube Series CMF-SD Type Ceramic Voltage - Max 230V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 200mA Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing - Report errors?		
Category Circuit Protection Package 4-SMD Cube Series CMF-SD Type Ceramic Voltage - Max 230V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Manufacturer Part Number	CMF-SD35-10-2
Package 4-SMD Cube Series CMF-SD Type Ceramic Voltage - Max 230V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Manufacturer	Bourns Inc.
Package 4-SMD Cube Series CMF-SD Type Ceramic Voltage - Max 230V (600V Int) Current - Max 3A Current - Hold (lh) (Max) 100mA Current - Trip (lt) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Category	Circuit Protection
Series CMF-SD Type Ceramic Voltage - Max 230V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -		PTC Resettable Fuses
Type Ceramic Voltage - Max 230V (600V Int) Current - Max 3A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Package	4-SMD Cube
Voltage - Max 230V (600V Int) Current - Max 3A Current - Hold (lh) (Max) 100mA Current - Trip (It) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Series	CMF-SD
Current - Max 3A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Type	Ceramic
Current - Hold (Ih) (Max) 100mA Current - Trip (It) 200mA Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Voltage - Max	230V (600V Int)
Current - Trip (It) Time to Trip 200ms Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) 35 Ohms Operating Temperature Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 200mA 200ms - Rounting Type 35 Ohms - 0.402" L x 0.354" W (10.20mm x 9.00mm) - 10.425" (10.80mm) - 10.425" (10.80mm) - 10.400	Current - Max	3A
Time to Trip 200ms Resistance - Initial (Ri) (Min) - Resistance - Post Trip (R1) (Max) - Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Current - Hold (Ih) (Max)	100mA
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) 35 Ohms Operating Temperature Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Current - Trip (It)	200mA
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) 35 Ohms Operating Temperature - Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Time to Trip	200ms
Resistance - 25°C (Typ) Operating Temperature Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Resistance - Initial (Ri) (Min)	-
Operating Temperature Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	-
Ratings - Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Resistance - 25°C (Typ)	35 Ohms
Mounting Type Surface Mount Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Operating Temperature	-
Package / Case 4-SMD Cube Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Ratings	-
Size / Dimension 0.402" L x 0.354" W (10.20mm x 9.00mm) Height - Seated (Max) - Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.425" (10.80mm) -	Package / Case	4-SMD Cube
Thickness (Max) 0.425" (10.80mm) Lead Spacing -	Size / Dimension	0.402" L x 0.354" W (10.20mm x 9.00mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.425" (10.80mm)
Report errors?	Lead Spacing	-
		Report errors?

CMF-SD35-10-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CMF-SD35-10-2 Payment Methods



















CMF-SD35-10-2 Shipping Methods













If you have any question about CMF-SD35-10-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com