

CMF5511K500BERE70

CMF5511K500BERE70 Information

Part Number CMF5511K500BERE70	
Manufacturer Vishay Dale	L 1939
Category Resistors Through Hole Resistors	nieri) Seite
Description RES 11.5K OHM 1/2W .1% AXIAL	27
Package Axial	:35
For the pricing/inventory/lead time, please contact us	/#*÷
For Reference Only Website: https://www.heisener.com E-mail: salesdept@heisener.com	quest a (

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Quote

CMF5511K500BERE70 Specifications

Manufacturer Part NumberCMF5511K500BERE70ManufacturerVishay DaleCategoryResistorsCategoryResistorsThrough Hole ResistorsPackageAxialSeriesCMFResistance11.5 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
CategoryResistorsCategoryResistorsThrough Hole ResistorsPackageAxialSeriesCMFResistance11.5 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyPoperating Temperature-55°C ~ 175°CPackage / CaseAxial
For a constraint of the sensition of the sensitient of the sensitient of the sensition of th
PackageAxialSeriesCMFResistance11.5 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature55°C ~ 175°CPackage / CaseAxial
SeriesCMFResistance11.5 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
Resistance11.5 kOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
Tolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
Temperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxial
Operating Temperature-55°C ~ 175°CPackage / CaseAxial
Package / Case Axial
Sumplier Device Deckage Aviel
Supplier Device Package Axial
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)
Height - Seated (Max) -
Number of Terminations 2
Failure Rate -
Report errors

CMF5511K500BERE70 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CMF5511K500BERE70 Payment Methods



If you have any question about CMF5511K500BERE70, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com