

CMF551M0000BEEK

CMF551M0000BEEK Information

| www.tells.myc.com | Part Number Manufacturer Category Description Package | Resistors Through Hole Resistors RES 1.00M OHM 1/2W .1% AXIAL Axial For the pricing/inventory/lead time, please contact us | |
|--------------------|---|---|-----------------|
| For Reference Only | | Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CMF551M0000BEEK Specifications

| Manufacturer Part Number CMF551M0000BEEK Manufacturer Vishay Dale Category Resistors Category Through Hole Resistors Package Axial Series CMF5 Resistance 1 MOhms Tolerance ±0.1% Power (Watts) 0.5W, 1/2W Composition Metal Film Features Flame Retardant Coating, Moisture Resistant, Safety Operating Temperature -55°C ~ 175°C Package / Case Axial Size / Dimension 0.09°D Dia x 0.240° L (2.29mm x 6.10mm) Height - Seated (Max) - Patherer Rate - | | |
|---|--------------------------|---|
| CategoryResistorsPackageAxialPackageAxialSeriesCMFResistance1 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFame Retardant Coating, Moisture Resistant, SafetyPoperature Coefficient±25pm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-Failure Rate< | Manufacturer Part Number | CMF551M0000BEEK |
| Through Hole ResistorsPackageAxialPackageCMFResistance1 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTomperature Coefficient±25ppm/°COperating TemperatureAxialSupplier Device PackageAxialSupplier Device Package0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate-Failure Ra | Manufacturer | Vishay Dale |
| PackageAxiaSeriesCMFResistance1 MOhmsTolerance±0.1%Power (Wats)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature±25ppm/°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.900° Dia x 0.240° L (2.29mm x 6.10mm)Height - Seated (Max)2Failure Rate-Failure Rate2 | Category | Resistors |
| SeriesCMFResistance1 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyOperating Temperature±25ppm/°COperating TemperatureAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)2Aumber of Terminations2Failure Rate- | | Through Hole Resistors |
| Resistance1 MOhmsTolerance $\pm 0.1\%$ Power (Watts) $0.5W, 1/2W$ CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient $\pm 25pm/^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 175^{\circ}C$ Package / CaseAxialSupplier Device Package 0.090° Dia x 0.240° L $(2.29mm x 6.10mm)$ Height - Seated (Max) 2 Number of Terminations 2 Failure Rate -1 | Package | Axial |
| Tolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device Package0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Aumber of Terminations2Failure Rate-Other Seated (Max)-State Seated (Max)- | Series | CMF |
| Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate- | Resistance | 1 MOhms |
| CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate- | Tolerance | $\pm 0.1\%$ |
| FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate- | Power (Watts) | 0.5W, 1/2W |
| Temperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate- | Composition | Metal Film |
| Operating Temperature-55°C ~ 175°CPackage / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate- | Features | Flame Retardant Coating, Moisture Resistant, Safety |
| Package / CaseAxialSupplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate- | Temperature Coefficient | ±25ppm/°C |
| Supplier Device PackageAxialSize / Dimension0.090" Dia x 0.240" L (2.29mm x 6.10mm)Height - Seated (Max)-Number of Terminations2Failure Rate- | Operating Temperature | -55°C ~ 175°C |
| Number of Terminations0.090" Dia x 0.240" L (2.29mm x 6.10mm)Failure Rate-Autor of Terminations-Construc | Package / Case | Axial |
| Height - Seated (Max)-Number of Terminations2Failure Rate- | Supplier Device Package | Axial |
| Number of Terminations2Failure Rate- | Size / Dimension | 0.090" Dia x 0.240" L (2.29mm x 6.10mm) |
| Failure Rate - | Height - Seated (Max) | - |
| | Number of Terminations | 2 |
| Report errors? | Failure Rate | - |
| Report citors: | | Report errors? |

CMF551M0000BEEK Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CMF551M0000BEEK Payment Methods



If you have any question about CMF551M0000BEEK, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com